

Tehnička pomoć:

info@tim-kabel.hr

Kontakti prodaja:

ZG: 01 5555 900, **ST:** 021 374 444, **OS:** 031 297 607

PVC-om izolirani instalacijski kabe i vodiči			str
H07V-U	P	▼	1
H07V-R	P/M	▼	1
H05V-K	P/F	▼	1
H07V-K	P/F	▼	1
H07V2-K	P/FT	▼	1
(N)YM	PP-Y	▼	1
NYiFY	PP/R	▼	2
H03VH-H	P/L	▼	2
H03VV-F	PP/L	▼	2
H05VV-F	PP/J	▼	2

EPR, PUR i silikonom izolirani kabe i vodiči			str
H05RR-F	GG/J	▼	5, 6
H07RN-F	GN/J	▼	6
H01N2-D		▼	6
H05RNH2-F		▼	6
NSSHöu	EPN-50	▼	6, 7
SiE		▼	7
SiHE		▼	7
H07BQ-F		▼	7

Upravljački i kabe i za elektroniku			str
LiYCY		▼	10
LiYCY-TP		▼	10
LiHCH			11
YSLY		▼	11, 12
YSLCY		▼	12, 13
BUS kabe i		▼	13
Kabe i za alarme		▼	13
Kabe i za zvučnike		▼	13

LAN kabe i			str
Cat.5e		▼	14
Cat 6, Cat 6A		▼	14
Cat 7		▼	14

Energetski kabe i 1 - 36 kV			str
E-YY	PP00	▼	2, 3
FG16(O)R16		▼	3, 4
NYCY	PP40	▼	4
NYCWX	PP40	▼	4, 5
NA2XY	XP00-A	▼	5
NFA2X	X00-A	▼	5
NA2XS(F)2Y 20 kV	XHE 49-A	▼	5
EAXeCWB 36 kV	XHE 49-A		5
Bakreno uže		▼	5
Fe/Zn traka			5

Kabe i bez halogena			str
H07Z-K		▼	7, 8
NHXMH		▼	8
N2XH		▼	8, 9
FG16OM16			9
NHXX E90		▼	9
BXO-HFTG	MPRX LKM-HF	▼	10
H1Z2Z2-K	Solarni kabe i	▼	10
Konektor MC4 SOLAR		▼	10

Telekomunikacijski i Koaksijalni kabe i			str
YYSch		▼	13
J-Y(St)Y	TI44	▼	13
JB-Y(St)Y		▼	13
J-H(St)Y		▼	13
JE-H(St)H E30-E90		▼	14
TK59(U) xDSL			14
F-2YA2Y	TK33	▼	14
Koax 75 Ω		▼	14
Koax 50 Ω		▼	14

Svjetlovodni kabe i			str
Multimode		▼	14
Singlemode		▼	14

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
H07V-U PVC-om izolirani vodič - jednožični (puni)						
	1.5	100	306	20	14.4	2,6 - 3,2
	2.5	100	493	31	24.0	3,2 - 3,9
	4	100	936	46	38.4	3,6 - 4,4
	6	100	1.373	65	57.6	4,1 - 5,0
	10	100	2.116	110	96.0	5,3 - 6,4
H07V-R PVC-om izolirani vodič - višezični						
	10	100	2.291	112	96	5,6 - 6,7
	16	razno	3.909	170	153.6	6,4 - 7,8
	25	razno	6.230	260	240.0	8,1 - 9,7
	35	razno	8.454	340	336.0	9,0 - 10,9
H05V-K PVC-om izolirani vodič - finožični						
	0.5	100	143	10	4.8	2,1 - 2,5
	0.75	100	191	12	7.2	2,2 - 2,7
	1	100	247	14	9.6	2,4 - 2,8
H07V-K PVC-om izolirani vodič - finožični						
	1.5	100	315	20	14.4	2,8 - 3,4
	2.5	100	513	31	24.0	3,4 - 4,1
	4	100	816	46	38.4	3,9 - 4,8
	6	100	1.173	65	57.6	4,4 - 5,3
	10	100	1.972	110	96.0	5,7 - 6,8
	16	100	3.120	170	153.6	6,7 - 8,1
	25	100, razno	4.969	260	240.0	8,4 - 10,2
	35	razno	6.941	360	336.0	9,7 - 11,7
	50	razno	10.503	515	480.0	11,5 - 13,9
	70	razno	14.426	710	672.0	13,2 - 16,0
	95	razno	19.293	940	912.0	15,1 - 18,2
	120	razno	24.581	1.180	1.152.0	16,7 - 20,2
	150	razno	31.174	1.600	1.440.0	18,6 - 22,5
	185	razno	36.765	2.100	1.776.0	20,6 - 24,9
	240	razno	49.649	3.015	2.304.0	23,5 - 28,4
H07V2-K PVC-om izolirani vodič - finožični, s povećanom otpornošću na toplinu						
	150	razno	41.681	1.534	1.440.0	19,2 - 21,2
(N)YM PVC-om izoliran i oplašten instalacijski kabel						
	2 x 1,5	100	841	115	28.8	8,4 - 9,8
	3 x 1,5	50, 100	991	135	43.2	8,8 - 10,5
	3 x 1,5	500	1.024	135	43.2	8,8 - 10,5
	4 x 1,5	100	1.372	160	57.6	9,5 - 11,0
	4 x 1,5	500	1.441	160	57.6	9,5 - 11,0
	5 x 1,5	50, 100	1.604	190	72.0	9,9 - 12,0
	5 x 1,5	500	1.695	190	72.0	9,9 - 12,0
	7 x 1,5	100, 500	2.687	235	100.8	11,0 - 13,0
	3 x 2,5	50, 100	1.550	190	72.0	10,0 - 11,5
	3 x 2,5	500	1.621	190	72.0	10,0 - 11,5
	4 x 2,5	100	2.168	230	96.0	11,0 - 12,5
	4 x 2,5	500	2.512	230	96.0	11,0 - 12,5
	5 x 2,5	50, 100	2.502	270	120.0	11,5 - 13,5
	5 x 2,5	500	2.616	270	120.0	11,5 - 13,5
	3 x 4	razno	2.944	265	115.2	11,5 - 13,0
	3 x 6	razno	4.449	315	172.8	12,0 - 15,0
	4 x 4	razno	4.125	330	153.6	12,5 - 14,5
	4 x 6	razno	6.013	460	230.4	14,5 - 16,5
	4 x 10	razno	10.464	690	384.0	16,5 - 19,0
	5 x 6	100, razno	6.195	540	288.0	15,5 - 18,0
	5 x 4	100, razno	4.319	410	192.0	14,0 - 16,5
	5 x 10	razno	10.923	870	480.0	18,5 - 21,5
NYiFY PVC-om izoliran i oplašten instalacijski plosnati kabel						
	3 x 1,5	100	1.237	102	43.2	15,5 x 4,0
	3 x 2,5	100	1.933	152	72.0	18,2 x 4,5

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
H03VH-H PVC-om izolirani fleksibilni plosnati kabel						
	2 x 0,75	100	417	26	14.4	2,8 x 5,7
H03VV-F PVC-om izoliran i oplašten laki finožični kabel						
	2 x 0,75	100, 500	421	48	14.4	4,9 - 6,3
	3 G 0,75	100, 500	590	57	21.6	5,2 - 6,7
	4 G 0,75	100	787	70	28.8	5,7 - 7,3
	5 G 0,75	100	990	87	36.0	7,0 - 7,4
H05VV-F PVC-om izoliran i oplašten finožični kabel						
	2 x 1	100	589	65	19.2	5,9 - 7,5
	3 G 1	100	836	80	28.8	6,3 - 8,0
	4 G 1	100	1.192	92	38.4	7,1 - 9,0
	5 G 1	100	1.476	113	48.0	7,8 - 9,8
	7 G 1	100	2.107	136	67.2	8,8 - 9,5
	2 x 1,5	100	782	90	28.8	6,8 - 8,6
	3 G 1,5	100, razno	1.058	115	43.2	7,4 - 9,4
	4 G 1,5	100	1.532	145	57.6	8,4 - 10,5
	5 G 1,5	100, razno	1.767	175	72.0	9,3 - 11,6
	7 G 1,5	100	2.849	195	100.8	10,6
	2 x 2,5	100	1.412	115	48.0	8,4 - 10,6
	3 G 2,5	100, razno	1.750	175	72.0	9,2 - 11,4
	4 G 2,5	100	2.505	210	96.0	10,1 - 12,5
	5 G 2,5	100	2.827	260	120.0	11,2 - 13,9
	5 G 4	razno	5.149	363	192.0	13,0 - 16,1
	5 G 6	razno	7.194	583	288.0	16,7
E-YY-O Energetski 0,6/1 kV kabel izoliran i oplašten PVC-om bez zaštitnog vodiča						
	1 x 16	razno	4.253	240	153.6	10,0 - 13,0
	1 x 25	razno	6.435	350	240.0	12,0 - 15,0
	1 x 35	razno	8.711	460	336.0	13,0 - 16,0
	1 x 50	razno	11.794	600	480.0	14,0 - 17,0
	1 x 70	razno	16.121	800	672.0	16,0 - 19,0
	1 x 95	razno	22.341	1.100	912.0	18,0 - 21,0
	1 x 120	razno	28.391	1.350	1.152.0	19,0 - 22,0
	1 x 150	razno	33.820	1.650	1.440.0	21,0 - 25,0
	1 x 185	razno	43.300	2.000	1.776.0	23,0 - 27,0
	1 x 240	razno	57.320	2.600	2.304.0	26,0 - 30,0
	1 x 300	razno	72.078	3.200	2.880.0	28,0 - 32,0
	2 x 1,5	razno	1.071	190	28.8	11,0 - 13,0
	2 x 2,5	razno	1.484	230	48.0	12,0 - 14,0
	2 x 4	razno	2.597	310	76.8	13,0 - 15,0
	2 x 6	razno	3.859	380	115.2	14,0 - 16,0
E-YY-J Energetski 0,6/1 kV kabel izoliran i oplašten PVC-om, sa zaštitnim vodičem						
	3 x 1,5	100, razno	1.136	190	43.2	11,0 - 14,0
	3 x 2,5	100, razno	1.694	240	72.0	12,0 - 15,0
	3 x 4	razno	3.177	330	115.2	14,0 - 17,0
	3 x 6	razno	4.577	420	172.8	15,0 - 18,0
	3 x 10	razno	8.049	580	288.0	17,0 - 20,0
	4 x 1,5	razno	1.640	220	57.6	12,0 - 16,0
	4 x 2,5	razno	2.406	290	96.0	13,0 - 17,0
	4 x 4	razno	3.951	400	153.6	15,0 - 19,0
	4 x 6	razno	6.000	510	230.4	16,0 - 20,0
	4 x 10 RM	razno	9.222	720	384.0	18,0 - 22,0
	4 x 16	razno	14.251	1.050	614.4	21,0 - 25,0
	4 x 25	razno	22.492	1.600	960.0	25,0 - 32,0
	4 x 35	razno	30.855	1.750	1.344.0	27,0 - 34,0
	4 x 50	razno	39.930	2.300	1.920.0	29,0 - 36,0
	4 x 70	razno	57.142	3.100	2.688.0	33,0 - 40,0
	4 x 95	razno	79.322	4.200	3.648.0	38,0 - 45,0
	4 x 120	razno	99.671	5.200	4.608.0	41,0 - 49,0
	4 x 150	razno	123.513	6.400	5.760.0	46,0 - 54,0
	4 x 185	razno	150.466	8.050	7.104.0	51,0 - 59,0
	4 x 240	razno	199.875	11.000	9.216.0	57,0 - 65,0
	5 x 1,5	razno	1.824	270	72.0	13,0 - 16,0

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
E-YY-J	5 x 2,5	razno	2.788	350	120.0	14,0 - 17,0
	5 x 4	razno	4.677	480	192.0	15,0 - 18,0
	5 x 6	razno	6.744	610	288.0	18,0 - 21,0
	5 x 10 RM	razno	10.811	880	480.0	19,0 - 22,0
	5 x 16	razno	16.744	1.250	768.0	22,0 - 25,0
	5 x 25	razno	27.801	1.950	1.200.0	27,0 - 33,0
	5 x 35	razno	37.193	2.400	1.680.0	33,0 - 40,0
	5 x 50	razno	55.265	3.500	2.400.0	39,0 - 45,0
	5 x 70	razno	78.338	4.450	3.360.0	41,0 - 47,0
	5 x 95	razno	108.232	6.134	4.560.0	46,0 - 52,0
E-YY-JZ Signalni 0,6/1 kV kabel izoliran i oplašten PVC-om						
	7 x 1,5	razno	3.071	300	100.8	14,1 - 17
	10 x 1,5	razno	5.236	360	144.0	17,2 - 21
	12 x 1,5	razno	5.859	400	172.8	17,7 - 22
	14 x 1,5	razno	7.341	450	201.6	18,5 - 23
	16 x 1,5	razno	7.740	500	230.4	19,4 - 24
	19 x 1,5	razno	9.769	560	273.6	20,3 - 25
	24 x 1,5	razno	10.270	700	345.6	22,9 - 28
	7 x 2,5	razno	5.099	420	168.0	15,9 - 18
	10 x 2,5	razno	8.329	500	240.0	19,6 - 22
	12 x 2,5	razno	9.340	560	288.0	20,2 - 23
	14 x 2,5	razno	11.532	630	336.0	21,0 - 24
	16 x 2,5	razno	13.684	710	384.0	22,0 - 25
	19 x 2,5	razno	15.131	830	456.0	23,0 - 26
	24 x 2,5	razno	18.057	1.050	576.0	26,9 - 30
FG16R16 Energetski fleksibilni 0,6/1 kV kabel izoliran HEPR gumom i oplašten PVC-om R16 kvalitete						
	1 x 25	razno	6.539	301	240.0	11.4
	1 x 35	razno	8.121	396	336.0	14.6
	1 x 50	razno	11.226	556	480.0	16.4
	1 x 70	razno	15.530	761	672.0	17.3
	1 x 95	razno	20.046	991	912.0	20.4
	1 x 120	razno	26.607	1.219	1.152.0	22.4
	1 x 150	razno	32.265	1.517	1.440.0	24.8
	1 x 185	razno	40.287	1.821	1.776.0	27.2
	1 x 240	razno	51.446	2.366	2.304.0	30.4
	1 x 300	razno	66.192	2.947	2.880.0	33.0
	1 x 400	razno	98.682	3.870	3.840.0	37.7
FG16OR16 Energetski fleksibilni 0,6/1 kV kabel izoliran HEPR gumom i oplašten PVC-om R16 kvalitete						
	2 x 1,5	razno	1.547	125	28.8	12.0
	2 x 2,5	razno	2.123	151	48.0	13.0
	2 x 4	razno	2.982	207	76.8	14.2
	2 x 6	razno	4.146	256	115.2	15.4
	2 x 10	razno	6.628	395	192.0	17.3
	3 G 1,5	razno	1.583	139	43.2	12.5
	3 G 2,5	razno	2.325	185	72.0	13.6
	3 G 4	razno	3.350	246	115.2	14.9
	3 G 6	razno	4.778	313	172.8	16.2
	3 G 10	razno	7.938	503	288.0	18.2
	3 x 35 + 1 G 25	razno	32.155	1611	1.248.0	29.2
	3 x 50 x 1 G 25	razno	43.370	2.142	1.680.0	32.4
	3 x 70 + 1 G 35	razno	58.569	3.037	2.352.0	37.0
	3 x 95 + 1 G 50	razno	79.124	4.047	3.216.0	42.0
	3 x 120 + 1 G 70	razno	107.928	5.327	4.128.0	46.9
	3 x 150 + 1 G 95	razno	148.662	6.635	5.232.0	52.5
	4 G 1,5	razno	2.223	171	57.6	13.4
	4 G 2,5	razno	2.931	222	96.0	14.6
	4 G 4	razno	4.640	297	153.6	16.0
	4 G 6	razno	6.920	392	230.4	17.5
	4 G 10	razno	10.594	611	384.0	19.8
	4 G 16	razno	15.661	886	614.4	22.4
	4 G 25	razno	24.101	1.255	960.0	26.8
	4 G 35	razno	35.298	1.750	1.344.0	30.5
	4 G 50	razno	50.179	2.530	1.920.0	34.1

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
FG16OR16	4 G 70	razno	70.834	3.600	2.688.0	36.6
	4 G 95	razno	93.769	4.380	3.648.0	41.5
	4 G 120	razno	119.185	5.585	4.608.0	45.8
	4 G 150	razno	149.336	6.920	5.760.0	52.1
	5 G 1,5	razno	2.524	204	72.0	14.4
	5 G 2,5	razno	3.485	266	120.0	15.6
	5 G 4	razno	5.266	361	192.0	17.3
	5 G 6	razno	7.377	471	288.0	18.9
	5 G 10	razno	12.521	756	480.0	21.5
	5 G 16	razno	18.657	1.119	768.0	24.4
	5 G 25	razno	28.832	1.597	1.200.0	29.3
	5 G 35	razno	39.837	2.140	1.680.0	32.8
	5 G 50	razno	60.571	3.030	2.400.0	38.2
	7 G 1,5	razno	3.941	247	100.8	15.4
	7 G 2,5	razno	5.697	381	168.0	16.8
12 G 1,5	razno	6.808	380	172.8	19.3	
NYCY	Energetski i signalni 0,6/1 kV kabel izoliran i oplašten PVC-om, s koncentričnim vodičem					
	2 x 1,5 / 1,5	razno	2.414	200	52.0	12 - 13
	3 x 1,5 / 1,5	razno	2.806	220	66.0	13 - 17
	4 x 1,5 / 1,5	razno	3.185	250	81.0	14 - 18
	5 x 1,5 / 1,5	razno	3.613	330	95.0	15 - 16
	7 x 1,5 / 2,5	razno	4.756	350	133.0	14 - 19
	12 x 1,5 / 2,5	razno	7.162	470	205.0	19 - 24
	16 x 1,5 / 4	razno	9.899	620	276.0	20
	19 x 1,5 / 4	razno	12.243	660	320.0	22 - 28
	24 x 1,5 / 6	razno	14.607	850	413.0	25 - 31
	30 x 1,5 / 6	razno	17.431	1.020	499.0	32
	2 x 2,5 / 2,5	razno	2.973	260	80.0	13,3 - 14
	3 x 2,5 / 2,5	razno	3.522	280	104.0	14 - 17
	4 x 2,5 / 2,5	razno	4.154	340	128.0	15 - 19
	5 x 2,5 / 2,5	razno	5.014	400	152.0	16 - 17
	7 x 2,5 / 2,5	razno	6.359	450	200.0	17 - 21
	10 x 2,5 / 4	razno	9.957	600	286.0	20 - 25
	12 x 2,5 / 4	razno	9.722	660	334.0	20 - 25
	16 x 2,5 / 6	razno	14.896	800	451.0	22.5
	19 x 2,5 / 6	razno	16.818	940	523.0	23 - 29
	21 x 2,5 / 6	razno	16.505	1.100	571.0	26
	24 x 2,5 / 6	razno	21.408	1.150	696.0	27 - 33
	2 x 4 / 4	razno	4.343	350	123.0	15,3 - 16,0
	3 x 4 / 4	razno	6.058	390	161.0	15 - 18
	4 x 4 / 4	razno	5.720	460	200.0	16 - 20
	5 x 4 / 4	razno	8.107	550	238.0	19
	2 x 6 / 6	razno	5.910	430	182.0	16,1 - 17,5
	3 x 6 / 6	razno	8.540	500	240.0	16 - 20
	4 x 6 / 6	razno	8.762	580	297.0	17 - 21
	5 x 6 / 6	razno	11.432	700	355.0	20 - 22
	4 x 10 / 10	razno	15.764	765	504.0	19 - 23
	4 x 16 / 16	razno	22.119	1.060	796.0	21 - 25
NYCWY	Energetski 0,6/1 kV PVC kabel, s valovitim koncentričnim Cu vodičem					
	4 x 10 / 10	razno	14.080	870	504	19 - 23
	4 x 16 / 16	razno	21.680	1.250	796	21 - 25
	4 x 25 / 16	razno	30.573	1.800	1.142	25 - 32
	4 x 35 / 16	razno	39.753	2.050	1.526	26 - 33
	4 x 50 / 25	razno	53.843	2.700	2.203	29 - 36
	4 x 70 / 35	razno	76.480	3.750	3.082	34 - 41
	4 x 95 / 50	razno	104.184	5.000	4.208	42 - 47
	4 x 120 / 70	razno	132.378	6.300	5.388	43 - 50
NA2XY	Energetski 0,6/1 kV kabel izoliran PVC-om i oplašten XLPE-om, s Al vodičima					
	1 x 70	razno	2.605	383	203.0	16 - 19
	1 x 95	razno	3.444	490	275.5	18 - 21
	1 x 120	razno	4.166	575	348.0	19 - 22
	1 x 150	razno	5.114	695	435.0	21 - 25
	1 x 185	razno	6.201	845	536.5	23 - 27
	1 x 240	razno	7.973	1.100	696.0	26 - 30

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
NA2XY	4 x 16	razno	3.013	750	185.6	21 - 25
	4 x 25	razno	4.293	950	290.0	25 - 32
	4 x 35	razno	5.800	1.141	406.0	27 - 34
	4 x 50	razno	7.519	1.242	580.0	29 - 36
	4 x 70	razno	10.340	1.631	812.0	33 - 40
	4 x 95	razno	12.804	2.063	1.102.0	38 - 45
	4 x 120	razno	16.211	2.538	1.392.0	41 - 49
	4 x 150	razno	18.998	3.090	1.740.0	46 - 54
	4 x 185	razno	24.052	3.838	2.146.0	51 - 59
4 x 240	razno	31.161	4.863	2.784.0	57 - 65	
NFA2X Samonosivi kabelski snop 0,6/1kV s XLPE-izolacijom						
NFA2X	2 x 16	razno	1.108	137	82.8	15
	4 x 16	razno	2.241	270	186.0	18
NA2XS(F)2Y 12/20 kV Srednjenaponski 12/20 kV kabel XLPE / PE, Aluminijski vodič ,uzdužno vodonepropustan						
NA2XS(F)2Y 12/20 kV	1 x 70 / 16		11.968	907	203,0 / 153,6	31
	1 x 95 / 16		13.036	1.304	275,5 / 153,6	33
	1 x 120 / 16		15.324	1.139	348,0 / 153,6	34
	1 x 150 / 25		17.066	1.251	435,0 / 240,0	36
	1 x 185 / 25		19.613	1.450	536,5 / 240,0	37
	1 x 240 / 25		21.170	1.698	696,0 / 240,0	40
	1 x 300 / 25		24.491	1.917	870,0 / 240,0	42
	1 x 400 / 35		29.971	2.336	1.160,0 / 336,0	45
	EAXeCWB 20,8/36 kV Srednjenaponski 20,8/36 kV kabel XLPE / PE, Aluminijski vodič ,uzdužno vodonepropustan					
EAXeCWB 20,8/36 kV	1 x 150 / 25		21.240	1.750	435,0 / 240,0	44
	1 x 185 / 25		23.508	1.950	536,5 / 240,0	46
	1 x 240 / 25		25.610	2.200	696,0 / 240,0	48
Bakreno uže Golo bakreno uže klase 3						
Bakreno uže	16	razno	3.196	142	142.0	5.1
	25	razno	5.297	217	217.0	6.3
	35	razno	7.027	308	308.0	7.5
	50	razno	8.881	443	443.0	9.0
	70	razno	14.177	590	590.0	10.5
	95	razno	20.168	836	836.0	12.5
Fe/Zn traka Pocinčana traka za gromobranske i slične sustave						
Fe/Zn traka	20 x 3	48 - 52	3.018			20 x 3
	25 x 4	48 - 52	2.916			25 x 4
	30 x 4	48 - 52	3.018			30 x 4
	40 x 4	48 - 52	3.018			40 x 4
	spojnica 60x60/3		2.222			60 x 60 x 3
	spojnica 80x80/3		2.980			80 x 80 x 3
H05RR-F Lakom EPR gumom optašten i izoliran fleksibilni kabel						
H05RR-F	2 x 0,75	100	817	63	14.4	5,7 - 8,2
	3 G 0,75	100	1.065	78	21.6	6,2 - 8,8
	2 x 1	100	1.000	73	19.2	6,1 - 8,8
	2 x 1,5	100	1.295	103	28.8	7,6 - 10,5
	3 G 1,5	100	1.544	125	43.2	8,0 - 11,0
	4 G 1,5	100	2.082	154	57.6	9,0 - 12,5
	5 G 1,5	100	2.599	182	72.0	9,8 - 13,5
	2 G 2,5	100	2.024	146	48.0	9,0 - 12,5
	3 G 2,5	100	2.313	177	72.0	9,6 - 13,0
	4 G 2,5	100	3.199	222	96.0	10,7 - 14,0
	5 G 2,5	100	3.811	269	120.0	11,9 - 15,5
	H07RN-F Teškom gumom optašten i gumom izoliran fleksibilni kabel					
H07RN-F	1 x 10	razno	3.287	204	96	9,5 - 11,9
	1 x 16	razno	4.686	286	153.6	10,8 - 13,4
	1 x 25	razno	6.922	390	240	12,7 - 15,8
	1 x 35	razno	9.466	523	336	14,3 - 17,9
	1 x 50	razno	13.443	699	480	16,5 - 20,6
	1 x 70	razno	18.391	950	672	18,6 - 23,3
	1 x 95	razno	24.282	1202	912	20,8 - 26,0
	1 x 120	razno	30.918	1524	1152	22,8 - 28,6
	1 x 150	razno	38.298	1839	1440	25,2 - 31,4
	1 x 185	razno	45.632	2184	1776	27,6 - 34,4
	1 x 240	razno	59.268	2840	2304	30,6 - 38,3

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
H07RN-F	1 x 300	razno	75.418	3413	2880	33,5 - 41,9
	2 x 1,5	razno	1.486	136	28.8	8,5 - 11,0
	3 G 1,5	100, razno	1.694	162	43.2	9,2 - 11,9
	4 G 1,5	100, razno	2.303	197	57.6	10,2 - 13,1
	5 G 1,5	100, razno	3.105	234	72.0	11,2 - 14,4
	7 G 1,5	razno	4.816	335	100.8	14,0 - 15,7
	12 G 1,5	razno	7.495	560	172.8	17,6 - 22,4
	19 G 1,5	razno	11.949	795	273.6	22,5 - 26,6
	24 G 1,5	razno	14.861	1.000	345.6	24,3 - 30,7
	2 G 2,5	razno	2.216	190	48.0	10,2 - 13,1
	3 G 2,5	100, razno	2.490	229	72.0	10,9 - 14,0
	4 G 2,5	100, razno	3.383	279	96.0	12,1 - 15,5
	5 G 2,5	100, razno	4.042	348	120.0	13,3 - 17,0
	7 G 2,5	razno	7.276	520	168.0	16,5 - 18,2
	12 G 2,5	razno	11.187	760	288.0	18,5 - 22,5
	19 G 2,5	razno	18.916	1.075	456.0	24,6 - 31,0
	24 G 2,5	razno	22.252	1.390	576.0	28,8 - 36,4
	3 G 4	razno	3.991	329	115.2	12,7 - 16,2
	3 G 6	razno	5.981	452	172.8	14,1 - 18,0
	3 G 10	razno	10.309	776	288.0	19,1 - 24,2
	4 G 4	razno	4.919	402	153.6	14,0 - 17,9
	4 G 6	razno	6.859	561	230.4	15,7 - 20,0
	4 G 10	razno	12.101	935	384.0	20,9 - 26,5
	4 G 16	razno	17.183	1.286	614.4	23,8 - 30,1
	4 G 25	razno	28.276	1.692	960.0	28,9 - 36,6
	4 G 35	razno	37.380	2.266	1.344.0	32,5 - 41,1
	4 G 50	razno	54.272	3.021	1.920.0	37,7 - 47,5
	4 G 70	razno	76.192	4.121	2.688.0	42,7 - 54,0
	4 G 95	razno	97.820	5.361	3.648.0	48,4 - 61,0
	5 G 4	razno	5.969	470	192.0	15,6 - 19,9
	5 G 6	razno	8.136	620	288.0	17,5 - 22,2
	5 G 10	razno	15.249	1.155	480.0	22,9 - 29,1
	5 G 16	razno	22.197	1.460	768.0	26,4 - 33,3
	5 G 25	razno	37.049	2.380	1.200.0	32,0 - 40,4
	5 G 35	razno	49.743	2.716	1.680.0	37,0 - 42,0
H01N2-D	Gumom oplošten kabel za zavarivanje, normalnog stupnja fleksibilnosti					
	1 x 16	razno	4.941	205	153.6	8,8 - 11,5
	1 x 25	razno	6.682	302	240.0	10,1 - 13,0
	1 x 35	razno	8.974	420	336.0	11,4 - 14,5
	1 x 50	razno	12.637	586	480.0	13,2 - 17,0
	1 x 70	razno	18.433	798	672.0	15,3 - 19,2
	1 x 95	razno	24.190	1.015	912.0	17,1 - 21,5
H05RNH2-F	Plosnati gumom oplošten kabel za ukrasnu rasvjetu					
	2 x 2,5	razno	3.697	147	48	5,7 x 13,3
NSSHöu	Gumom izoliran i oplošten 0,6/1 kV kabel za jača mehanička opterećenja i rudnike					
	3 x 1,5	razno	3.840	195	43.2	11.9
	4 x 1,5	razno	4.967	226	57.6	12.7
	5 x 1,5	razno	5.606	264	72.0	13.6
	3 x 2,5	razno	5.415	257	72.0	13.3
	4 x 2,5	razno	6.713	343	96.0	15.5
	5 x 2,5	razno	7.378	402	120.0	16.6
	4 x 4	razno	10.099	440	153.6	17.1
	4 x 6	razno	13.089	549	230.4	18.5
	4 x 10	razno	20.935	855	384.0	22.8
	4 x 16	razno	31.111	1.224	614.4	26.7
	4 x 25	razno	44.188	1.802	960.0	31.9
	4 x 35	razno	59.845	2.230	1.344.0	33.7
	4 x 50	razno	80.455	3.201	1.920.0	40.9
	5 x 4	razno	11.986	521	192.0	18.4
	5 x 6	razno	16.889	694	288.0	20.8
	5 x 10	razno	26.939	1.027	480.0	24.6
SiF	Silikonskom gumom izoliran finožični vodič					
	0.5	100	232	8.6	4.8	2.1
	0.75	100	340	11	7.2	2.4

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
SiF	1	100	414	13.6	9.6	2.4
	1.5	100	518	20	14.4	2.8
	2.5	100	824	32	24.0	3.4
	4	100	1.399	49	38.4	4.2
	6	100	2.062	71	57.6	5.2
	10	100	3.568	124	96.0	7
	16	100	6.085	188	153.6	8
	25	100	9.535	296	240.0	9.9
	35	100	13.077	400	336.0	11.2
SiHF Silikonskom gumom izoliran i oplašten fleksibilni kabel						
SiHF	2 x 0,75	razno	1.102	57	14.4	6.4
	3 x 0,75	razno	1.526	66	21.6	6.8
	3 x 1	razno	1.802	78	28.8	7.4
	2 x 1,5	razno	1.665	87	28.8	7.6
	3 x 1,5	razno	2.338	98	43.2	8.0
	4 x 1,5	razno	3.092	122	57.6	8.8
	5 x 1,5	razno	4.287	148	72.0	9.6
	7 x 1,5	razno	5.803	232	100.8	10.9
	3 x 2,5	razno	3.573	152	72.0	9.6
	4 x 2,5	razno	4.771	189	96.0	10.6
	5 x 2,5	razno	6.840	229	120.0	11.6
	H07BQ-F Poliuretanom oplašten fleksibilni energetski kabel za gradilišta					
H07BQ-F	2 x 1,5	razno	1.965	87.5	28.8	7,6 - 9,8
	3 x 1,5	razno	2.628	107	43.2	8,0 - 10,4
	4 x 1,5	razno	3.122	136	57.6	9,0 - 11,6
	5 x 1,5	razno	3.631	170	72.0	9,8 - 12,7
	3 x 2,5	razno	3.643	159	72.0	9,6 - 12,4
	4 x 2,5	razno	4.750	206	96.0	10,7 - 13,8
	5 x 2,5	razno	6.097	258	120.0	11,9 - 15,3
	3 x 4	razno	5.809	228	115.2	11,3 - 14,5
	5 x 4	razno	9.128	345	192.0	14,1 - 17,9
	5 x 6	razno	13.027	518	288.0	15,7 - 20,0
H07Z-K Bezhalogeni finožični vodič, poboljšanih svojstava za slučaj požara						
H07Z-K	1.5	100	421	20	14.4	2,8 - 3,5
	2.5	100	669	31	24.0	3,4 - 4,3
	4	100	1.014	46	38.4	3,9 - 4,9
	6	100	1.467	65	57.6	4,4 - 5,5
	10	100	2.496	110	96.0	5,7 - 7,1
	16	razno	3.807	170	153.6	6,7 - 8,4
	25	razno	5.862	260	240.0	8,4 - 10,6
	35	razno	8.135	360	336.0	9,7 - 12,1
	50	razno	11.647	515	480.0	11,5 - 14,4
	70	razno	16.258	710	672.0	13,2 - 16,6
	95	razno	21.529	940	912.0	15,2 - 18,8
	120	razno	27.406	1.180	1.152.0	16,7 - 20,9
	150	razno	33.525	1.600	1.440.0	18,6 - 23,3
	185	razno	42.278	2.100	1.776.0	20,6 - 25,8
	240	razno	55.800	3.015	2.304.0	23,5 - 29,4
NHXMH Bezhalogeni instalacijski kabel, 300/500V, poboljšanih svojstava za slučaj požara						
NHXMH	2 x 1,5	500	1.061	120	28.8	9.0
	3 x 1,5	500	1.319	133	43.2	9.8
	4 x 1,5	500	1.959	157	57.6	10.5
	5 x 1,5	500	2.244	183	72.0	11.5
	7 x 1,5	500	3.731	250	100.8	11
	3 x 2,5	500	1.927	176	72.0	11
	5 x 2,5	500	3.347	249	120.0	12.5
	3 x 4	razno	3.603	247	115.2	12.5
	3 x 6	razno	5.351	335	172.8	14
	5 x 4	razno	5.908	370	192.0	15.5
	5 x 6	razno	8.435	488	288.0	16.5
	5 x 10	razno	12.880	739	480.0	18
	5 x 16	razno	20.774	1.142	768.0	23
	N2XH Bezhalogeni energetski i signalni 0,6/1 kV kabel, poboljšanih svojstava za slučaj požara					
N2XH	1 x 16	razno	4.889	202	154.0	9.1

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
N2XH	1 x 25	razno	7.174	302	240.0	11
	1 x 35	razno	9.658	397	336.0	12
	1 x 50	razno	13.084	523	480.0	13
	1 x 70	razno	17.815	745	672.0	15
	1 x 95	razno	25.316	986	912.0	17
	1 x 120	razno	27.810	1.214	1.152.0	18
	1 x 150	razno	34.818	1.536	1.440.0	21
	1 x 185	razno	42.860	1.888	1.776.0	23
	1 x 240	razno	55.588	2.472	2.304.0	26
	1 x 300	razno	66.551	2.945	2.880.0	28
	2 x 1,5	razno	1.244	120	29.0	9
	2 x 2,5	razno	1.847	154	48.0	10
	3 x 1,5	razno	1.412	135	43.0	9
	3 x 2,5	razno	1.972	181	72.0	10
	3 x 4	razno	3.238	242	115.0	11
	3 x 6	razno	5.048	319	173.0	13
	3 x 10	razno	8.723	464	288.0	14
	4 x 1,5	razno	2.012	163	58.0	10
	4 x 2,5	razno	2.997	214	96.0	11
	4 x 4	razno	4.625	294	154.0	12
	4 x 6	razno	6.649	390	230.0	14
	4 x 10	razno	11.522	586	384.0	16
	4 x 16	razno	17.707	874	614.0	19
	4 x 25	razno	25.902	1.332	960.0	23
	4 x 35	razno	35.340	1.777	1.344.0	26
	4 x 50	razno	47.262	2.343	1.920.0	29
	4 x 70	razno	67.020	3.384	2.688.0	35
	4 x 95	razno	91.918	4.490	3.648.0	39
	4 x 120	razno	114.798	5.558	4.608.0	43
	4 x 150	razno	136.358	6.998	5.760.0	48
	4 x 185	razno	168.076	8.657	7.104.0	53
	4 x 240	razno	214.319	11.385	9.216.0	60
	5 x 1,5	razno	2.176	193	72.0	11
	5 x 2,5	razno	3.223	256	120.0	12
	5 x 4	razno	5.373	352	192.0	13
5 x 6	razno	7.480	475	288.0	15	
5 x 10	razno	11.894	708	480.0	17	
5 x 16	razno	18.901	1.081	768.0	21	
5 x 25	razno	28.341	1.631	1.200.0	26	
5 x 35	razno	42.579	2.163	1.680.0	29	
7 x 1,5	razno	3.574	300	100.8	15	
10 x 1,5	razno	5.582	360	144	19	
12 x 1,5	razno	6.526	400	172.8	20	
7 x 2,5	razno	7.790	420	168	16	
FG16OM16	Bezhalogeni 0,6/1 kV kabel izoliran visokokvalitetnom G16 HEPR smjesom					
	3 G 1,5	razno	1.699	139	43.2	12.5
	3 G 2,5	razno	2.496	185	72.0	13.6
	3 G 4	razno	3.628	246	115.2	14.9
	3 G 6	razno	5.192	313	172.8	16.2
	3 G 10	razno	8.291	503	288.0	18.2
	3 G 16	razno	12.530	609	460.8	20.6
	5 G 1,5	razno	2.613	204	72.0	14.4
	5 G 2,5	razno	3.852	266	120.0	15.6
	5 G 4	razno	5.711	361	192.0	17.3
	5 G 6	razno	8.252	471	288.0	18.9
	5 G 10	razno	13.293	756	480.0	21.5
	5 G 16	razno	20.170	1.119	768.0	24.4
NHXX FE180 / E90	Bezhalogeni 0,6/1 kV kabel, s električnom funkcijom od 90 min					
	1 x 25	razno	7.565	347	240.0	11.7
	1 x 35	razno	9.959	449	336.0	12.8
	1 x 50	razno	12.968	589	480.0	14.3
	1 x 70	razno	20.029	810	672.0	16.1
	1 x 95	razno	24.138	1.090	912.0	18.5
	1 x 120	razno	33.873	1.318	1.152.0	19.6

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
NHXH FE180 / E90	1 x 150	razno	36.339	1.648	1.440.0	21.8
	1 x 185	razno	47.765	2.029	1.776.0	24
	1 x 240	razno	66.465	2.658	2.304.0	27.2
	2 x 1,5	razno	1.631	178	29.0	11
	3 x 1,5	razno	2.122	200	43.0	11.5
	3 x 2,5	razno	3.099	250	72.0	12.4
	3 x 4	razno	4.602	319	115.0	13.5
	3 x 6	razno	6.493	403	173.0	14.6
	4 x 1,5	razno	3.029	234	58.0	12.4
	4 x 2,5	razno	3.993	296	96.0	13.4
	4 x 4	razno	6.137	381	154.0	14.6
	4 x 6	razno	8.364	490	230.0	15.8
	4 x 10	razno	13.950	695	384.0	17.8
	4 x 16	razno	21.006	1.089	614.0	22.1
	4 x 25	razno	33.066	1.618	960.0	26.3
	4 x 35	razno	43.088	2.083	1.344.0	29
	4 x 50	razno	55.983	2.752	1.920.0	32.8
	4 x 70	razno	79.389	3.804	2.688.0	37.6
	4 x 95	razno	107.809	5.092	3.648.0	43.1
	4 x 120	razno	133.395	6.133	4.608.0	46
	4 x 150	razno	169.212	7.662	5.760.0	51.2
	4 x 185	razno	211.390	9.425	7.104.0	56.5
	4 x 240	razno	276.336	12.334	9.216.0	64.1
	5 x 1,5	razno	3.467	278	72.0	13.4
	5 x 2,5	razno	4.653	353	120.0	14.5
	5 x 4	razno	6.970	456	192.0	15.8
	5 x 6	razno	9.614	589	288.0	17.2
5 x 10	razno	15.687	832	480.0	19.3	
5 x 16	razno	23.423	1.361	768.0	24.8	
5 x 25	razno	35.723	1.960	1.200.0	28.8	
5 x 35	razno	52.176	2.547	1.680.0	32	
7 x 1,5	razno	4.747	331	101.0	15.8	
7 x 2,5	razno	7.853	426	168.0	17.7	
BXO-HFTG		Brodski teškogorivi kabel bez halogena 0,6/1 kV				
	3 x 1,5	razno	2.193	120	43.2	9
	3 x 2,5	razno	3.247	160	72.0	10
H1Z2Z2-K		Kabel za fotonaponske sustave, AC/DC 1500 V				
	1 x 4	500	1.132	58.2	38.4	6.6
	1 x 6	500	1.615	79	57.6	7.4
	1 x 10	500	2.682	128	96.0	8.8
SOLAR MC4 konektor		Konektori za PV kabele				
	4 F 1000 V (4 ... 6mm ²)	100	1.277	9.5		
	4 M 1000 V (4 ... 6mm ²)	100	1.277	11		
	4 F GEN2 1500 V (4 ... 6mm ²)	100	1.329	11.2		
	4 M GEN2 1500 V (4 ... 6mm ²)	100	1.329	13.1		
LIYCY		Elektronički fleksibilni kabel izoliran i oplašten PVC-om, s Cu opletom				
	2 x 0,25	razno	584	28	16.0	4.6
	3 x 0,25	razno	586	34	21.0	4.8
	4 x 0,25	razno	878	40	24.0	5.2
	5 x 0,25	razno	1.021	47	29.0	5.7
	6 x 0,25	razno	1.208	54	32.0	6.3
	7 x 0,25	razno	1.143	61	37.0	6.3
	8 x 0,25	razno	1.584	66	42.0	6.4
	10 x 0,25	razno	1.914	80	50.0	6.7
	2 x 0,5	100, razno	763	35	23.0	5.2
	3 x 0,5	100, razno	1.061	55	39.0	5.3
	4 x 0,5	100, razno	1.270	61	46.0	5.7
	5 x 0,5	razno	1.596	76	57.0	6.4
	7 x 0,5	razno	2.265	98	80.0	7
	10 x 0,5	razno	2.723	135	100.0	8.8
	12 x 0,5	razno	3.320	157	117.0	9.5
	2 x 0,75	100, razno	771	59	38.0	5.7
	3 x 0,75	100, razno	1.122	66	50.0	5.9
	4 x 0,75	100, razno	1.353	77	58.0	6.5

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
LiYCY	5 x 0,75	100, razno	1.758	93	70.0	7
	7 x 0,75	100, razno	2.431	130	100.0	7.8
	8 x 0,75	razno	2.825	145	110.0	8.6
	10 x 0,75	razno	4.732	180	140.0	9.7
	12 x 0,75	razno	4.052	202	154.0	10.2
	2 x 1	100, razno	1.037	65	46.0	6
	3 x 1	100, razno	1.577	80	56.0	6.5
	4 x 1	100, razno	1.745	98	69.0	7.1
	5 x 1	100, razno	2.450	127	89.0	7.8
	7 x 1	razno	3.090	158	118.0	8.5
	8 x 1	razno	3.864	197	130.0	9.4
	10 x 1	razno	5.390	232	145.0	10.8
	12 x 1	razno	5.540	260	168.0	11.2
	2 x 1,5	100, razno	1.433	88	63.0	7.7
	3 x 1,5	100, razno	2.055	100	76.0	7.9
	4 x 1,5	100, razno	2.634	126	108.0	8
	5 x 1,5	razno	3.456	160	129.0	8.8
	7 x 1,5	razno	4.304	208	164.0	9.6
	LiYCY-TP	Elektronički PVC fleksibilni kabel, s Cu opletom, s uvijenim paricama				
	2 x 2 x 0,5	razno	1.536	93	54.0	7.3
	3 x 2 x 0,5	razno	1.819	129	74.0	8.4
	4 x 2 x 0,5	razno	2.589	146	91.0	9.4
	6 x 2 x 0,5	razno	4.685	198	120.0	11.2
	8 x 2 x 0,5	razno	5.805	259	144.0	11.5
	12 x 2 x 0,5	razno	6.702	354	199.0	15.1
	2 x 2 x 0,75	razno	1.872	106	58.0	9.5
	3 x 2 x 0,75	razno	2.450	140	85.0	9.6
	4 x 2 x 0,75	razno	2.953	179	108.0	10.3
	6 x 2 x 0,75	razno	6.068	246	146.0	12.4
LiHCH	Elektronički bezhalogeni fleksibilni kabel, s Cu opletom					
	2 x 0,75	razno	889	59	38.0	5.7
	3 x 0,75	razno	1.132	66	50.0	5.9
	4 x 0,75	razno	1.369	77	58.0	6.5
	5 x 0,75	razno	1.740	93	70.0	7
	7 x 0,75	razno	2.310	130	100.0	7.8
	2 x 1	razno	1.025	65	46.0	6
	3 x 1	razno	1.377	80	56.0	6.5
	4 x 1	razno	1.791	98	69.0	7.1
	5 x 1	razno	2.169	127	89.0	7.8
	7 x 1	razno	2.947	158	118.0	8.5
	2 x 1,5	razno	1.409	88	63.0	7.7
	3 x 1,5	razno	1.871	100	76.0	7.9
	4 x 1,5	razno	2.434	126	108.0	8
	5 x 1,5	razno	2.970	160	129.0	8.8
	7 x 1,5	razno	4.031	208	164.0	9.6
YSLY	Signalni fleksibilni kabel izoliran i oplašten PVC-om					
	2 x 0,5	razno	391	35	9.6	4.8
	3 x 0,5	razno	582	41	14.0	5.1
	4 x 0,5	razno	719	49	19.0	5.5
	5 x 0,5	razno	963	60	24.0	6.2
	7 x 0,5	razno	1.182	77	34.0	6.7
	10 x 0,5	razno	1.801	101	48.0	8.5
	12 x 0,5	razno	1.962	125	58.0	9.1
	14 x 0,5	razno	2.693	131	67.0	9.5
	16 x 0,5	razno	2.674	151	77.0	10.3
	21 x 0,5	razno	3.971	215	101.0	11.2
	25 x 0,5	razno	4.411	252	120.0	12.6
	2 x 0,75	razno	509	42	14.0	5.2
	3 x 0,75	razno	681	51	22.0	5.5
	4 x 0,75	razno	901	63	29.0	6.2
	5 x 0,75	razno	1.142	78	36.0	6.7
	6 x 0,75	razno	1.521	85	43.0	7.3
	7 x 0,75	razno	1.600	95	50.0	7.5
	10 x 0,75	razno	2.410	150	72.0	9.6

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
YSLY	12 x 0,75	razno	2.747	165	86.0	9.8
	16 x 0,75	razno	3.726	195	115.0	11.1
	21 x 0,75	razno	5.091	288	151.0	12.5
	25 x 0,75	razno	5.987	330	180.0	14
	34 x 0,75	razno	8.396	435	245.0	16.3
	2 x 1	razno	668	52	19.0	5.6
	3 x 1	razno	898	65	29.0	6.1
	4 x 1	razno	1.176	78	38.0	6.7
	5 x 1	razno	1.482	95	48.0	7.5
	7 x 1	razno	2.042	120	67.0	8.1
	10 x 1	razno	3.062	180	96.0	10.2
	12 x 1	razno	3.390	235	115.0	10.9
	14 x 1	razno	3.759	238	134.0	11.2
	16 x 1	razno	4.845	266	154.0	11.9
	18 x 1	razno	5.436	298	173.0	12.9
	21 x 1	razno	6.599	366	202.0	13.8
	25 x 1	razno	7.319	400	240.0	15.4
	34 x 1	razno	10.785	535	326.0	17.9
	2 x 1,5	razno	912	65	29.0	6.4
	3 x 1,5	razno	1.151	80	43.0	6.8
	4 x 1,5	razno	1.577	102	58.0	7.6
	5 x 1,5	razno	1.961	125	72.0	8.3
	7 x 1,5	razno	2.739	166	101.0	9.2
	10 x 1,5	razno	4.193	243	144.0	11.6
	12 x 1,5	razno	4.942	272	173.0	12.4
	14 x 1,5	razno	6.058	323	202.0	12.7
	16 x 1,5	razno	6.532	361	230.0	13.4
	18 x 1,5	razno	7.716	402	259.0	14.8
	21 x 1,5	razno	8.706	484	302.0	15.6
	25 x 1,5	razno	10.345	555	360.0	17.6
	34 x 1,5	razno	14.408	750	490.0	20.2
	2 x 2,5	razno	1.463	99	48.0	7.6
	3 x 2,5	razno	1.997	128	72.0	8.3
	4 x 2,5	razno	2.627	159	96.0	9
	5 x 2,5	razno	3.235	199	120.0	10.1
	7 x 2,5	razno	4.650	258	168.0	11.2
10 x 2,5	razno	6.880	310	240.0	13	
12 x 2,5	razno	8.444	361	288.0	15	
18 x 2,5	razno	12.501	519	432.0	18	
3 x 4	razno	3.155	169	115.0	10	
4 x 4	razno	4.275	242	154.0	11	
4 x 6	razno	6.262	340	230.0	13	
4 x 10	razno	10.440	577	384.0	17	
4 x 16	razno	17.116	1.022	614.0	21	
5 x 4	razno	5.468	302	192.0	12.5	
5 x 6	razno	8.196	424	288.0	14	
5 x 10	razno	13.913	717	480.0	18.5	
5 x 16	razno	21.462	1.370	768.0	22.5	
7 x 4	razno	7.481	407	269.0	13.4	
7 x 6	razno	11.212	600	403.0	16	
YSLCY	Signalni fleksibilni PVC kabel, sa Cu zaslonom					
	2 x 0,75	razno	1.096	59	39.0	6.2
	3 x 0,75	razno	1.293	66	49.0	6.2
	4 x 0,75	razno	1.538	77	57.0	6.7
	5 x 0,75	razno	2.021	93	70.0	7.4
	7 x 0,75	razno	2.525	130	98.0	8.6
	12 x 0,75	razno	3.971	202	151.0	10.7
	16 x 0,75	razno	5.353	275	172.0	12
	25 x 0,75	razno	7.708	415	271.0	15.6
	34 x 0,75	razno	11.441	535	370.0	17.2
	2 x 1	razno	1.214	65	55.0	6.7
	3 x 1	razno	1.569	80	70.0	7
	4 x 1	razno	1.979	98	80.0	7.1
	5 x 1	razno	2.320	127	95.0	8.5

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
YSLCY	7 x 1	razno	3.184	158	120.0	9.7
	10 x 1	razno	4.241	232	138.0	12
	12 x 1	razno	4.847	260	186.0	12.4
	14 x 1	razno	6.197	302	198.0	13
	18 x 1	razno	6.633	380	245.0	14.5
	25 x 1	razno	8.558	534	342.0	18
	2 x 1,5	razno	1.439	88	65.0	7.3
	3 x 1,5	razno	2.019	100	90.0	7.7
	4 x 1,5	razno	2.405	126	110.0	8.3
	5 x 1,5	razno	3.109	160	125.0	9.4
	7 x 1,5	razno	4.024	208	159.0	10.7
	12 x 1,5	razno	6.701	338	254.0	13.6
	18 x 1,5	razno	9.263	479	367.0	16.3
	25 x 1,5	razno	13.624	705	492.0	20.3
	2 x 2,5	razno	2.120	130	98.0	9
	3 x 2,5	razno	3.253	167	148.0	9.9
	4 x 2,5	razno	3.688	195	174.0	10.2
	5 x 2,5	razno	4.927	223	200.0	11.6
	7 x 2,5	razno	6.658	344	235.0	13.7
	12 x 2,5	razno	9.473	570	440.0	18.2
	4 x 4	razno	5.838	310	290.0	12.9
	4 x 6	razno	8.211	415	360.0	14.7
	4 x 10	razno	13.127	731	535.0	18.9
	4 x 16	razno	19.415	993	809.0	20.8
	5 x 4	razno	6.565	385	328.0	14.3
	5 x 6	razno	9.112	509	441.0	16.4
BUS kabele		Kabele za Profibus i KNX sustave				
	BUS PB 1 x 2 x 0,64	razno	2.343	74	30.1	8.0
	BUS EIB / KNX 2 x 2 x 0,8	razno	769	54	21.0	6.6
Kabel za alarme		Kabel za alarme				
	4 x 0,22	100	312	21	8.45	3.6
	6 x 0,22	100	315	26	12.67	4.1
	8 x 0,22	100	496	33	16.90	4.5
	12 x 0,22	100	634	45	25.34	5.35
	4 x 0,22 + 2 x 0,5	100	461	35	18.05	4.65
	6 x 0,22 + 2 x 0,75	razno	661	50	27.07	5.35
	12 x 0,22 + 2 x 0,75	razno	1.040	66	38.74	6.3
Kabel za zvučnike		Kabel za zvučnike				
	2 x 0,5	100	197	21	9.6	2,4 x 4,8
	2 x 0,75	100	250	29	14.0	2,5 x 5,0
	2 x 1	100	407	32	19.0	2,6 x 5,2
	2 x 1,5	100	532	42	29.0	2,7 x 5,6
	2 x 2,5	100	892	61	48.0	3,6 x 7,4
	2 x 4	100	1.717	110	77.0	4,5 x 9,7
YYSch		Telekomunikacijski instalacijski kabel s izolacijom i plaštom od PVC-a				
	2 x 0,6	100	282	12	5.6	3,1 - 3,7
	3 x 0,6	100	392	16	8.4	3,4 - 3,9
	4 x 0,6	100	495	20	11.2	3,5 - 4,1
	5 x 0,6	100	594	26	14.0	4,1 - 4,3
	6 x 0,6	100	695	29	16.8	4,6 - 4,7
	10 x 0,6	100	1.112	54	28.0	5,5 - 6,7
J-Y(St)Y		Telekomunikacijski instalacijski PVC kabel, sa zaslonom od Al-folije				
	1 x 2 x 0,6	250	305	30	7.0	5.0
	2 x 2 x 0,6	250	450	40	13.0	5.5
	3 x 2 x 0,6	250	692	50	18.0	6.3
	4 x 2 x 0,6	100, 250	773	60	24.0	6.8
	5 x 2 x 0,6	100, 250	1.031	70	30.0	7.2
	6 x 2 x 0,6	100	1.199	80	35.0	7.5
	10 x 2 x 0,6	razno	1.893	110	58.0	9.0
	20 x 2 x 0,6	razno	3.536	190	116.0	11.0
	30 x 2 x 0,6	razno	5.662	280	172.0	13.0
	50 x 2 x 0,6	razno	8.637	440	286.0	17.0
	100 x 2 x 0,6	razno	17.279	850	568.0	23.0
	1 x 2 x 0,8	250	432	40	11.0	6.0

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
J-Y(St)Y	2 x 2 x 0,8	100, 250, 500	637	60	21.0	7.0
	3 x 2 x 0,8	100, 250	1.020	80	31.0	8.5
	4 x 2 x 0,8	100, 250	1.267	100	41.0	9.0
	5 x 2 x 0,8	100, 250	1.729	120	52.0	9.5
	6 x 2 x 0,8	100	2.039	140	62.0	10.5
	10 x 2 x 0,8	razno	3.268	210	102.0	13.0
	20 x 2 x 0,8	razno	6.146	380	204.0	16.5
	30 x 2 x 0,8	razno	9.517	550	304.0	20.0
JB-Y(St)Y Vatrodojavni instalacijski PVC kabel, sa zaslonom od Al-folije						
JB-Y(St)Y	1 x 2 x 0,8	100, 500	409	40	11.0	6.0
	2 x 2 x 0,8	100, 500	630	60	21.0	7.0
	4 x 2 x 0,8	500, razno	1.357	100	41.0	9.0
J-H(St)Y Bezhalogeni telekomunikacijski kabel, poboljšanih svojstava za slučaj požara						
J-H(St)Y	2 x 2 x 0,8	razno	829	69	25.0	7.0
	2 x 2 x 0,8 (crveni)	razno	828	69	25.0	7.0
	4 x 2 x 0,8	razno	1.623	136	45.0	9.0
	4 x 2 x 0,8 (crveni)	razno	1.623	136	45.0	9.0
JE-H(St)H FE180 / E30-E90 Bezhalogeni kabel za industrijsku elektroniku, s funkcijom od 30 i 90 minuta						
JE-H(St)H FE180 / E30-E90	1 x 2 x 0,8	razno	859	40	15.0	5.5
	2 x 2 x 0,8	razno	1.217	56	25.0	6.6
	4 x 2 x 0,8	razno	2.414	96	45.0	8.7
TK 59-50 xDSL Telekom, distributivni kabel, vanjski, niskofrekventni za širokopolasne usluge						
TK 59-50 xDSL	2 x 2 x 0,5	razno	849	55	7.0	7.5
	6 x 2 x 0,5	razno	1.598	95	20.8	9.8
	10 x 2 x 0,5	razno	2.524	125	34.8	11.0
	20 x 2 x 0,5	razno	4.531	200	69.5	12.9
	50 x 2 x 0,5	razno	9.882	270	173.8	17.8
TK 59U-50 xDSL Telekom, samonosivi distributivni kabel, niskofrekventni za širokopolasne usluge						
TK 59U-50 xDSL	6 x 2 x 0,5	razno	2.269	130	20.8	9,4 x 16,7
F-2YA2Y Telekomunikacijski kabel za vanjsku uporabu, podzemni						
F-2YA2Y	2 x 2 x 0,8	razno	972	55	25	7.3
	6 x 2 x 0,8	razno	2.373	115	62	10.4
	10 x 2 x 0,8	razno	3.661	170	102	12.0
Koax 75 Ohm Koaksijalni kabel 75 Ohm						
Koax 75 Ohm	CATV 1,13/4,8 AF Tri-Shld	100, 500	724	50	18.5	6.8
	CATV 1,13/4,8 AF Tri-Shld LSOH	100	828	50	18.5	6.8
	RG 6	100	248	41	15.0	6.8
	RG 11	razno	1.593	135	62.6	10.1
	RG 59 B/U	100	484	54	24.7	6.15
	KOAX6 CT 15 A PE podzemni	razno	2.571	102	56.0	10.1
Koax 50 Ohm Koaksijalni kabel 50 Ohm						
Koax 50 Ohm	RG 58 C/U 50 Ohm	100	704	37	20	4.95
	RG 213 U 50 Ohm	razno	3.067	157	87	10.3
Cat.5e 200 Mhz LAN kabel kategorije 5e, do 200 MHz						
Cat.5e 200 Mhz	U/UTP PVC	305, 500	486	35	17.5	4,9 - 5,1
	U/UTP LSOH	500	567	36	17.5	4,9 - 5,1
	F/UTP PVC	500	636	36	19.8	5,9 - 6,6
	F/UTP LSOH	500	725	37	19.8	5,9 - 6,6
	SF/UTP LSOH	500	1.075	47	27	6,4 - 6,6
	U/UTP PE outdoor	500	748	39	12	7.5
	F/UTP PE outdoor	500	932	39	12	7.5
	U/UTP flex	500	755	26	11	5.2
	F/UTP flex	500	901	26	12	5.4
Cat. 6 350 Mhz LAN kabel kategorije 6, do 350 MHz						
Cat. 6 350 Mhz	U/UTP PVC	305, 500	607	39	20.5	6,2 - 6,8
	U/UTP LSOH	500	642	40	20.5	6,2 - 6,8
	U/FTP PVC	500	850	41	24.0	6,5 - 7,6
	U/FTP LSOH	500	876	44	24.0	6,5 - 7,6
	S/FTP LSOH	500	1.101	49	34.0	7,4 - 8,2
	U/UTP PE outdoor	500	864	39	20.5	7.5
Cat. 6A 500 Mhz LAN kabel kategorije 6A, do 500 MHz						
Cat. 6A 500 Mhz	U/FTP LSOH	500	972	44	24.0	6.5
Cat. 7 800 Mhz LAN kabel kategorije 7, do 800 MHz						
Cat. 7 800 Mhz	S/FTP LSOH	500	1.066	55	26.0	7,3 - 8,0

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
Cat. 7 800 Mhz	S/FTP PE outdoor	500	1.599	62	26.0	8.3
Multimode Svjetlovodni Unitube kabel sa MM nitima, s ojačanjem i zaštitom od glodavaca						
	4 G 50 / 125 OM2	razno	825	40		5.8
	8 G 50 / 125 OM2	razno	1.168	40		5.8
	12 G 50 / 125 OM2	razno	1.508	40		5.8
	24 G 50 / 125 OM2	razno	2.764	45		6.9
	4 G 50 / 125 OM3	razno	1.234	40		5.8
	8 G 50 / 125 OM3	razno	2.419	40		5.8
Singlemode Svjetlovodni kabel s SM nitima, Unitube / Stranded loose tube, za vanjsku upotrebu						
	1 x 4E9 / 125 4 niti G.657a	razno	779	7		2.5
	3 x 4E9 / 125 12 niti G.652d	razno	768	75		9.6
	6 x 4E9 / 125 24 niti G.652d	razno	996	78		9.6
	6 x 8E9 / 125 48 niti G.652d	razno	1.554	97		11.3
	8 x 12E9 / 125 96 niti G.652d	razno	4.272	97		11.8