

Tehnička pomoć:

info@tim-kabel.hr

Kontakti prodaja:**ZG:** 01 5555 900, **ST:** 021 374 444, **OS:** 031 297 607

PVC-om izolirani instalacijski kabe i vodiči			str
H07V-U	P	▼	1
H07V-R	P/M	▼	1
H05V-K	P/F	▼	1
H07V-K	P/F	▼	1
H07V2-K	P/FT	▼	1
(N)YM	PP-Y	▼	1
NYiFY	PP/R	▼	2
H03VH-H	P/L	▼	2
H03VV-F	PP/L	▼	2
H05VV-F	PP/J	▼	2

EPR, PUR i silikonom izolirani kabe i vodiči			str
H05RR-F	GG/J	▼	5, 6
H07RN-F	GN/J	▼	6
H01N2-D		▼	6
H05RNH2-F		▼	6
NSSHöu	EPN-50	▼	6, 7
SiF		▼	7
SiHF		▼	7
H07BQ-F		▼	7

Upravljački i kabe i za elektroniku			str
LiYCY		▼	10
LiYCY-TP		▼	10
LiHCH			11
YSLY		▼	11, 12
YSLCY		▼	12, 13
BUS kabe i		▼	13
Kabe i za alarme		▼	13
Kabe i za zvučnike		▼	13

LAN kabe i			str
Cat.5e		▼	14
Cat 6, Cat 6A		▼	14
Cat 7		▼	14

Energetski kabe i 1 - 36 kV			str
E-YY	PP00	▼	2, 3
FG16(O)R16		▼	3, 4
NYCY	PP40	▼	4
NYCWX	PP40	▼	4, 5
NA2XY	XP00-A	▼	5
NFA2X	X00-A	▼	5
NA2XS(F)2Y 20 kV	XHE 49-A	▼	5
EAXeCWB 36 kV	XHE 49-A		5
Bakreno uže		▼	5
Fe/Zn traka			5

Kabe i bez halogena			str
H07Z-K		▼	7, 8
NHXMH		▼	8
N2XH		▼	8, 9
FG16OM16			9
NHXH E90		▼	9
BXO-HFTG	MPRX LKM-HF	▼	10
H1Z2Z2-K	Solarni kabe i	▼	10
Konektor MC4 SOLAR		▼	10

Telekomunikacijski i Koaksijalni kabe i			str
YYSch		▼	13
J-Y(St)Y	TI44	▼	13
JB-Y(St)Y		▼	13
J-H(St)Y		▼	13
JE-H(St)H E30-E90		▼	14
TK59(U) xDSL			14
F-2YA2Y	TK33	▼	14
Koax 75 Ω		▼	14
Koax 50 Ω		▼	14

Svjetlovodni kabe i			str
Multimode		▼	14
Singlemode		▼	14

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
H07V-U PVC-om izolirani vodič - jednožični (puni)						
	1.5	100	303	20	14.4	2,6 - 3,2
	2.5	100	487	31	24.0	3,2 - 3,9
	4	100	926	46	38.4	3,6 - 4,4
	6	100	1.358	65	57.6	4,1 - 5,0
	10	100	2.092	110	96.0	5,3 - 6,4
H07V-R PVC-om izolirani vodič - višezžični						
	10	100	2.267	112	96	5,6 - 6,7
	16	razno	3.868	170	153.6	6,4 - 7,8
	25	razno	6.167	260	240.0	8,1 - 9,7
	35	razno	8.368	340	336.0	9,0 - 10,9
H05V-K PVC-om izolirani vodič - finožični						
	0.5	100	142	10	4.8	2,1 - 2,5
	0.75	100	189	12	7.2	2,2 - 2,7
	1	100	244	14	9.6	2,4 - 2,8
H07V-K PVC-om izolirani vodič - finožični						
	1.5	100	312	20	14.4	2,8 - 3,4
	2.5	100	508	31	24.0	3,4 - 4,1
	4	100	807	46	38.4	3,9 - 4,8
	6	100	1.160	65	57.6	4,4 - 5,3
	10	100	1.951	110	96.0	5,7 - 6,8
	16	100	3.086	170	153.6	6,7 - 8,1
	25	100, razno	4.914	260	240.0	8,4 - 10,2
	35	razno	6.863	360	336.0	9,7 - 11,7
	50	razno	10.386	515	480.0	11,5 - 13,9
	70	razno	14.262	710	672.0	13,2 - 16,0
	95	razno	19.076	940	912.0	15,1 - 18,2
	120	razno	24.306	1.180	1.152.0	16,7 - 20,2
	150	razno	30.826	1.600	1.440.0	18,6 - 22,5
	185	razno	36.348	2.100	1.776.0	20,6 - 24,9
	240	razno	49.092	3.015	2.304.0	23,5 - 28,4
H07V2-K PVC-om izolirani vodič - finožični, s povećanom otpornošću na toplinu						
	150	razno	41.315	1.534	1.440.0	19,2 - 21,2
(N)YM PVC-om izoliran i oplašten instalacijski kabel						
	2 x 1,5	100	833	115	28.8	8,4 - 9,8
	3 x 1,5	50, 100	981	135	43.2	8,8 - 10,5
	3 x 1,5	500	1.015	135	43.2	8,8 - 10,5
	4 x 1,5	100	1.358	160	57.6	9,5 - 11,0
	4 x 1,5	500	1.427	160	57.6	9,5 - 11,0
	5 x 1,5	50, 100	1.588	190	72.0	9,9 - 12,0
	5 x 1,5	500	1.678	190	72.0	9,9 - 12,0
	7 x 1,5	100, 500	2.662	235	100.8	11,0 - 13,0
	3 x 2,5	50, 100	1.534	190	72.0	10,0 - 11,5
	3 x 2,5	500	1.605	190	72.0	10,0 - 11,5
	4 x 2,5	100	2.145	230	96.0	11,0 - 12,5
	4 x 2,5	500	2.486	230	96.0	11,0 - 12,5
	5 x 2,5	50, 100	2.475	270	120.0	11,5 - 13,5
	5 x 2,5	500	2.588	270	120.0	11,5 - 13,5
	3 x 4	razno	2.915	265	115.2	11,5 - 13,0
	3 x 6	razno	4.404	315	172.8	12,0 - 15,0
	4 x 4	razno	4.084	330	153.6	12,5 - 14,5
	4 x 6	razno	5.951	460	230.4	14,5 - 16,5
	4 x 10	razno	10.358	690	384.0	16,5 - 19,0
	5 x 6	100, razno	6.129	540	288.0	15,5 - 18,0
	5 x 4	100, razno	4.276	410	192.0	14,0 - 16,5
	5 x 10	razno	10.813	870	480.0	18,5 - 21,5
NYiFY PVC-om izoliran i oplašten instalacijski plosnati kabel						
	3 x 1,5	100	1.226	102	43.2	15,5 x 4,0
	3 x 2,5	100	1.914	152	72.0	18,2 x 4,5

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
H03VH-H PVC-om izolirani fleksibilni plosnati kabel						
	2 x 0,75	100	413	26	14.4	2,8 x 5,7
H03VV-F PVC-om izoliran i oplašten laki finožični kabel						
	2 x 0,75	100, 500	417	48	14.4	4,9 - 6,3
	3 G 0,75	100, 500	584	57	21.6	5,2 - 6,7
	4 G 0,75	100	780	70	28.8	5,7 - 7,3
	5 G 0,75	100	982	87	36.0	7,0 - 7,4
H05VV-F PVC-om izoliran i oplašten finožični kabel						
	2 x 1	100	584	65	19.2	5,9 - 7,5
	3 G 1	100	828	80	28.8	6,3 - 8,0
	4 G 1	100	1.182	92	38.4	7,1 - 9,0
	5 G 1	100	1.463	113	48.0	7,8 - 9,8
	7 G 1	100	2.088	136	67.2	8,8 - 9,5
	2 x 1,5	100	775	90	28.8	6,8 - 8,6
	3 G 1,5	100, razno	1.049	115	43.2	7,4 - 9,4
	4 G 1,5	100	1.517	145	57.6	8,4 - 10,5
	5 G 1,5	100, razno	1.751	175	72.0	9,3 - 11,6
	7 G 1,5	100	2.822	195	100.8	10,6
	2 x 2,5	100	1.398	115	48.0	8,4 - 10,6
	3 G 2,5	100, razno	1.733	175	72.0	9,2 - 11,4
	4 G 2,5	100	2.480	210	96.0	10,1 - 12,5
	5 G 2,5	100	2.799	260	120.0	11,2 - 13,9
	5 G 4	razno	5.095	363	192.0	13,0 - 16,1
	5 G 6	razno	7.118	583	288.0	16,7
E-YY-O Energetski 0,6/1 kV kabel izoliran i oplašten PVC-om bez zaštitnog vodiča						
	1 x 16	razno	4.210	240	153.6	10,0 - 13,0
	1 x 25	razno	6.370	350	240.0	12,0 - 15,0
	1 x 35	razno	8.619	460	336.0	13,0 - 16,0
	1 x 50	razno	11.663	600	480.0	14,0 - 17,0
	1 x 70	razno	15.942	800	672.0	16,0 - 19,0
	1 x 95	razno	22.098	1.100	912.0	18,0 - 21,0
	1 x 120	razno	28.076	1.350	1.152.0	19,0 - 22,0
	1 x 150	razno	33.437	1.650	1.440.0	21,0 - 25,0
	1 x 185	razno	42.815	2.000	1.776.0	23,0 - 27,0
	1 x 240	razno	56.691	2.600	2.304.0	26,0 - 30,0
	1 x 300	razno	71.291	3.200	2.880.0	28,0 - 32,0
	2 x 1,5	razno	1.063	190	28.8	11,0 - 13,0
	2 x 2,5	razno	1.470	230	48.0	12,0 - 14,0
	2 x 4	razno	2.574	310	76.8	13,0 - 15,0
	2 x 6	razno	3.826	380	115.2	14,0 - 16,0
E-YY-J Energetski 0,6/1 kV kabel izoliran i oplašten PVC-om, sa zaštitnim vodičem						
	3 x 1,5	100, razno	1.126	190	43.2	11,0 - 14,0
	3 x 2,5	100, razno	1.677	240	72.0	12,0 - 15,0
	3 x 4	razno	3.148	330	115.2	14,0 - 17,0
	3 x 6	razno	4.534	420	172.8	15,0 - 18,0
	3 x 10	razno	7.971	580	288.0	17,0 - 20,0
	4 x 1,5	razno	1.626	220	57.6	12,0 - 16,0
	4 x 2,5	razno	2.383	290	96.0	13,0 - 17,0
	4 x 4	razno	3.913	400	153.6	15,0 - 19,0
	4 x 6	razno	5.943	510	230.4	16,0 - 20,0
	4 x 10 RM	razno	9.132	720	384.0	18,0 - 22,0
	4 x 16	razno	14.107	1.050	614.4	21,0 - 25,0
	4 x 25	razno	22.265	1.600	960.0	25,0 - 32,0
	4 x 35	razno	30.530	1.750	1.344.0	27,0 - 34,0
	4 x 50	razno	39.485	2.300	1.920.0	29,0 - 36,0
	4 x 70	razno	56.511	3.100	2.688.0	33,0 - 40,0
	4 x 95	razno	78.465	4.200	3.648.0	38,0 - 45,0
	4 x 120	razno	98.575	5.200	4.608.0	41,0 - 49,0
	4 x 150	razno	122.144	6.400	5.760.0	46,0 - 54,0
	4 x 185	razno	148.816	8.050	7.104.0	51,0 - 59,0
	4 x 240	razno	197.710	11.000	9.216.0	57,0 - 65,0
	5 x 1,5	razno	1.808	270	72.0	13,0 - 16,0

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)	
E-YY-J	5 x 2,5	razno	2.760	350	120.0	14,0 - 17,0	
	5 x 4	razno	4.633	480	192.0	15,0 - 18,0	
	5 x 6	razno	6.678	610	288.0	18,0 - 21,0	
	5 x 10 RM	razno	10.702	880	480.0	19,0 - 22,0	
	5 x 16	razno	16.571	1.250	768.0	22,0 - 25,0	
	5 x 25	razno	27.519	1.950	1.200.0	27,0 - 33,0	
	5 x 35	razno	36.800	2.400	1.680.0	33,0 - 40,0	
	5 x 50	razno	54.659	3.500	2.400.0	39,0 - 45,0	
	5 x 70	razno	77.490	4.450	3.360.0	41,0 - 47,0	
	5 x 95	razno	107.081	6.134	4.560.0	46,0 - 52,0	
E-YY-JZ Signalni 0,6/1 kV kabel izoliran i oplašten PVC-om							
E-YY-JZ	7 x 1,5	razno	3.045	300	100.8	14,1 - 17	
	10 x 1,5	razno	5.196	360	144.0	17,2 - 21	
	12 x 1,5	razno	5.812	400	172.8	17,7 - 22	
	14 x 1,5	razno	7.282	450	201.6	18,5 - 23	
	16 x 1,5	razno	7.675	500	230.4	19,4 - 24	
	19 x 1,5	razno	9.692	560	273.6	20,3 - 25	
	24 x 1,5	razno	10.181	700	345.6	22,9 - 28	
	7 x 2,5	razno	5.052	420	168.0	15,9 - 18	
	10 x 2,5	razno	8.257	500	240.0	19,6 - 22	
	12 x 2,5	razno	9.262	560	288.0	20,2 - 23	
	14 x 2,5	razno	11.432	630	336.0	21,0 - 24	
	16 x 2,5	razno	13.569	710	384.0	22,0 - 25	
	19 x 2,5	razno	15.005	830	456.0	23,0 - 26	
	24 x 2,5	razno	17.901	1.050	576.0	26,9 - 30	
	FG16R16 Energetski fleksibilni 0,6/1 kV kabel izoliran HEPR gumom i oplašten PVC-om R16 kvalitete						
	FG16R16	1 x 25	razno	6.476	301	240.0	11.4
1 x 35		razno	8.040	396	336.0	14.6	
1 x 50		razno	11.112	556	480.0	16.4	
1 x 70		razno	15.371	761	672.0	17.3	
1 x 95		razno	19.834	991	912.0	20.4	
1 x 120		razno	26.327	1.219	1.152.0	22.4	
1 x 150		razno	31.927	1.517	1.440.0	24.8	
1 x 185		razno	39.858	1.821	1.776.0	27.2	
1 x 240		razno	50.900	2.366	2.304.0	30.4	
1 x 300		razno	65.491	2.947	2.880.0	33.0	
1 x 400		razno	97.723	3.870	3.840.0	37.7	
FG16OR16 Energetski fleksibilni 0,6/1 kV kabel izoliran HEPR gumom i oplašten PVC-om R16 kvalitete							
FG16OR16	2 x 1,5	razno	1.538	125	28.8	12.0	
	2 x 2,5	razno	2.108	151	48.0	13.0	
	2 x 4	razno	2.960	207	76.8	14.2	
	2 x 6	razno	4.113	256	115.2	15.4	
	2 x 10	razno	6.574	395	192.0	17.3	
	3 G 1,5	razno	1.573	139	43.2	12.5	
	3 G 2,5	razno	2.308	185	72.0	13.6	
	3 G 4	razno	3.322	246	115.2	14.9	
	3 G 6	razno	4.736	313	172.8	16.2	
	3 G 10	razno	7.868	503	288.0	18.2	
	3 x 35 + 1 G 25	razno	31.840	1611	1.248.0	29.2	
	3 x 50 + 1 G 25	razno	42.941	2.142	1.680.0	32.4	
	3 x 70 + 1 G 35	razno	57.986	3.037	2.352.0	37.0	
	3 x 95 + 1 G 50	razno	78.322	4.047	3.216.0	42.0	
	3 x 120 + 1 G 70	razno	106.851	5.327	4.128.0	46.9	
	3 x 150 + 1 G 95	razno	147.190	6.635	5.232.0	52.5	
	4 G 1,5	razno	2.207	171	57.6	13.4	
	4 G 2,5	razno	2.908	222	96.0	14.6	
	4 G 4	razno	4.600	297	153.6	16.0	
	4 G 6	razno	6.858	392	230.4	17.5	
	4 G 10	razno	10.498	611	384.0	19.8	
	4 G 16	razno	15.512	886	614.4	22.4	
	4 G 25	razno	23.863	1.255	960.0	26.8	
	4 G 35	razno	34.959	1.750	1.344.0	30.5	

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
FG16OR16	4 G 50	razno	49.694	2.530	1.920.0	34.1
	4 G 70	razno	70.156	3.600	2.688.0	36.6
	4 G 95	razno	92.847	4.380	3.648.0	41.5
	4 G 120	razno	118.022	5.585	4.608.0	45.8
	4 G 150	razno	147.881	6.920	5.760.0	52.1
	5 G 1,5	razno	2.506	204	72.0	14.4
	5 G 2,5	razno	3.457	266	120.0	15.6
	5 G 4	razno	5.220	361	192.0	17.3
	5 G 6	razno	7.310	471	288.0	18.9
	5 G 10	razno	12.406	756	480.0	21.5
	5 G 16	razno	18.479	1.119	768.0	24.4
	5 G 25	razno	28.547	1.597	1.200.0	29.3
	5 G 35	razno	39.438	2.140	1.680.0	32.8
	5 G 50	razno	59.965	3.030	2.400.0	38.2
	7 G 1,5	razno	3.914	247	100.8	15.4
	7 G 2,5	razno	5.655	381	168.0	16.8
	12 G 1,5	razno	6.757	380	172.8	19.3
	NYCY	Energetski i signalni 0,6/1 kV kabel izoliran i oplašten PVC-om, s koncentričnim vodičem				
	2 x 1,5 / 1,5	razno	2.398	200	52.0	12 - 13
	3 x 1,5 / 1,5	razno	2.788	220	66.0	13 - 17
	4 x 1,5 / 1,5	razno	3.164	250	81.0	14 - 18
	5 x 1,5 / 1,5	razno	3.586	330	95.0	15 - 16
	7 x 1,5 / 2,5	razno	4.722	350	133.0	14 - 19
	12 x 1,5 / 2,5	razno	7.104	470	205.0	19 - 24
	16 x 1,5 / 4	razno	9.824	620	276.0	20
	19 x 1,5 / 4	razno	12.150	660	320.0	22 - 28
	24 x 1,5 / 6	razno	14.498	850	413.0	25 - 31
	30 x 1,5 / 6	razno	17.289	1.020	499.0	32
	2 x 2,5 / 2,5	razno	2.951	260	80.0	13,3 - 14
	3 x 2,5 / 2,5	razno	3.493	280	104.0	14 - 17
	4 x 2,5 / 2,5	razno	4.122	340	128.0	15 - 19
	5 x 2,5 / 2,5	razno	4.972	400	152.0	16 - 17
	7 x 2,5 / 2,5	razno	6.304	450	200.0	17 - 21
	10 x 2,5 / 4	razno	9.879	600	286.0	20 - 25
	12 x 2,5 / 4	razno	9.637	660	334.0	20 - 25
	16 x 2,5 / 6	razno	14.768	800	451.0	22.5
	19 x 2,5 / 6	razno	16.674	940	523.0	23 - 29
	21 x 2,5 / 6	razno	16.362	1.100	571.0	26
	24 x 2,5 / 6	razno	21.215	1.150	696.0	27 - 33
	2 x 4 / 4	razno	4.308	350	123.0	15,3 - 16,0
	3 x 4 / 4	razno	6.013	390	161.0	15 - 18
	4 x 4 / 4	razno	5.669	460	200.0	16 - 20
	5 x 4 / 4	razno	8.044	550	238.0	19
	2 x 6 / 6	razno	5.858	430	182.0	16,1 - 17,5
	3 x 6 / 6	razno	8.470	500	240.0	16 - 20
	4 x 6 / 6	razno	8.680	580	297.0	17 - 21
	5 x 6 / 6	razno	11.333	700	355.0	20 - 22
	4 x 10 / 10	razno	15.628	765	504.0	19 - 23
	4 x 16 / 16	razno	21.905	1.060	796.0	21 - 25
NYCWY	Energetski 0,6/1 kV PVC kabel, s valovitim koncentričnim Cu vodičem					
	4 x 10 / 10	razno	13.944	870	504	19 - 23
	4 x 16 / 16	razno	21.466	1.250	796	21 - 25
	4 x 25 / 16	razno	30.265	1.800	1.142	25 - 32
	4 x 35 / 16	razno	39.342	2.050	1.526	26 - 33
	4 x 50 / 25	razno	53.249	2.700	2.203	29 - 36
	4 x 70 / 35	razno	75.650	3.750	3.082	34 - 41
	4 x 95 / 50	razno	103.051	5.000	4.208	42 - 47
	4 x 120 / 70	razno	130.927	6.300	5.388	43 - 50
NA2XY	Energetski 0,6/1 kV kabel izoliran PVC-om i oplašten XLPE-om, s Al vodičima					
	1 x 70	razno	2.579	383	203.0	16 - 19
	1 x 95	razno	3.408	490	275.5	18 - 21
	1 x 120	razno	4.121	575	348.0	19 - 22

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
NA2XY	1 x 150	razno	5.060	695	435.0	21 - 25
	1 x 185	razno	6.134	845	536.5	23 - 27
	1 x 240	razno	7.884	1.100	696.0	26 - 30
	4 x 16	razno	2.990	750	185.6	21 - 25
	4 x 25	razno	4.257	950	290.0	25 - 32
	4 x 35	razno	5.749	1.141	406.0	27 - 34
	4 x 50	razno	7.448	1.242	580.0	29 - 36
	4 x 70	razno	10.239	1.631	812.0	33 - 40
	4 x 95	razno	12.672	2.063	1.102.0	38 - 45
	4 x 120	razno	16.041	2.538	1.392.0	41 - 49
	4 x 150	razno	18.798	3.090	1.740.0	46 - 54
	4 x 185	razno	23.799	3.838	2.146.0	51 - 59
	4 x 240	razno	30.834	4.863	2.784.0	57 - 65
	NFA2X Samonosivi kabelski snop 0,6/1kV s XLPE-izolacijom					
	2 x 16	razno	1.096	137	82.8	15
	4 x 16	razno	2.218	270	186.0	18
NA2XS(F)2Y 12/20 kV Srednjenaponski 12/20 kV kabel XLPE / PE, Aluminijski vodič ,uzdužno vodonepropustan						
	1 x 70 / 16		11.900	907	203,0 / 153,6	31
	1 x 95 / 16		12.959	1.304	275,5 / 153,6	33
	1 x 120 / 16		15.229	1.139	348,0 / 153,6	34
	1 x 150 / 25		16.945	1.251	435,0 / 240,0	36
	1 x 185 / 25		19.479	1.450	536,5 / 240,0	37
	1 x 240 / 25		21.017	1.698	696,0 / 240,0	40
	1 x 300 / 25		24.317	1.917	870,0 / 240,0	42
	1 x 400 / 35		29.735	2.336	1.160,0 / 336,0	45
EAXeCWB 20,8/36 kV Srednjenaponski 20,8/36 kV kabel XLPE / PE, Aluminijski vodič ,uzdužno vodonepropustan						
	1 x 150 / 25		21.119	1.750	435,0 / 240,0	44
	1 x 185 / 25		23.374	1.950	536,5 / 240,0	46
	1 x 240 / 25		25.457	2.200	696,0 / 240,0	48
Bakreno uže Golo bakreno uže klase 3						
	16	razno	3.163	142	142.0	5.1
	25	razno	5.242	217	217.0	6.3
	35	razno	6.954	308	308.0	7.5
	50	razno	8.790	443	443.0	9.0
	70	razno	14.031	590	590.0	10.5
	95	razno	19.960	836	836.0	12.5
Fe/Zn traka Pocinčana traka za gromobranske i slične sustave						
	20 x 3	48 - 52	3.018			20 x 3
	25 x 4	48 - 52	2.916			25 x 4
	30 x 4	48 - 52	3.018			30 x 4
	40 x 4	48 - 52	3.018			40 x 4
	spojnica 60x60/3		2.222			60 x 60 x 3
	spojnica 80x80/3		2.980			80 x 80 x 3
H05RR-F Lakom EPR gumom optašten i izoliran fleksibilni kabel						
	2 x 0,75	100	813	63	14.4	5,7 - 8,2
	3 G 0,75	100	1.060	78	21.6	6,2 - 8,8
	2 x 1	100	994	73	19.2	6,1 - 8,8
	2 x 1,5	100	1.287	103	28.8	7,6 - 10,5
	3 G 1,5	100	1.533	125	43.2	8,0 - 11,0
	4 G 1,5	100	2.066	154	57.6	9,0 - 12,5
	5 G 1,5	100	2.580	182	72.0	9,8 - 13,5
	2 G 2,5	100	2.011	146	48.0	9,0 - 12,5
	3 G 2,5	100	2.295	177	72.0	9,6 - 13,0
	4 G 2,5	100	3.173	222	96.0	10,7 - 14,0
	5 G 2,5	100	3.780	269	120.0	11,9 - 15,5
H07RN-F Teškom gumom optašten i gumom izoliran fleksibilni kabel						
	1 x 10	razno	3.262	204	96	9,5 - 11,9
	1 x 16	razno	4.646	286	153.6	10,8 - 13,4
	1 x 25	razno	6.859	390	240	12,7 - 15,8
	1 x 35	razno	9.378	523	336	14,3 - 17,9
	1 x 50	razno	13.317	699	480	16,5 - 20,6
	1 x 70	razno	18.210	950	672	18,6 - 23,3

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)	
H07RN-F	1 x 95	razno	24.036	1202	912	20,8 - 26,0	
	1 x 120	razno	30.616	1524	1152	22,8 - 28,6	
	1 x 150	razno	37.910	1839	1440	25,2 - 31,4	
	1 x 185	razno	45.153	2184	1776	27,6 - 34,4	
	1 x 240	razno	58.647	2840	2304	30,6 - 38,3	
	1 x 300	razno	74.642	3413	2880	33,5 - 41,9	
	2 x 1,5	razno	1.478	136	28.8	8,5 - 11,0	
	3 G 1,5	100, razno	1.683	162	43.2	9,2 - 11,9	
	4 G 1,5	100, razno	2.288	197	57.6	10,2 - 13,1	
	5 G 1,5	100, razno	3.084	234	72.0	11,2 - 14,4	
	7 G 1,5	razno	4.788	335	100.8	14,0 - 15,7	
	12 G 1,5	razno	7.447	560	172.8	17,6 - 22,4	
	19 G 1,5	razno	11.874	795	273.6	22,5 - 26,6	
	24 G 1,5	razno	14.767	1.000	345.6	24,3 - 30,7	
	2 G 2,5	razno	2.202	190	48.0	10,2 - 13,1	
	3 G 2,5	100, razno	2.471	229	72.0	10,9 - 14,0	
	4 G 2,5	100, razno	3.358	279	96.0	12,1 - 15,5	
	5 G 2,5	100, razno	4.011	348	120.0	13,3 - 17,0	
	7 G 2,5	razno	7.231	520	168.0	16,5 - 18,2	
	12 G 2,5	razno	11.111	760	288.0	18,5 - 22,5	
	19 G 2,5	razno	18.789	1.075	456.0	24,6 - 31,0	
	24 G 2,5	razno	22.097	1.390	576.0	28,8 - 36,4	
	3 G 4	razno	3.961	329	115.2	12,7 - 16,2	
	3 G 6	razno	5.933	452	172.8	14,1 - 18,0	
	3 G 10	razno	10.233	776	288.0	19,1 - 24,2	
	4 G 4	razno	4.881	402	153.6	14,0 - 17,9	
	4 G 6	razno	6.803	561	230.4	15,7 - 20,0	
	4 G 10	razno	12.007	935	384.0	20,9 - 26,5	
	4 G 16	razno	17.037	1.286	614.4	23,8 - 30,1	
	4 G 25	razno	28.030	1.692	960.0	28,9 - 36,6	
	4 G 35	razno	37.043	2.266	1.344.0	32,5 - 41,1	
	4 G 50	razno	53.778	3.021	1.920.0	37,7 - 47,5	
	4 G 70	razno	75.486	4.121	2.688.0	42,7 - 54,0	
	4 G 95	razno	96.875	5.361	3.648.0	48,4 - 61,0	
	5 G 4	razno	5.923	470	192.0	15,6 - 19,9	
	5 G 6	razno	8.068	620	288.0	17,5 - 22,2	
	5 G 10	razno	15.128	1.155	480.0	22,9 - 29,1	
	5 G 16	razno	22.008	1.460	768.0	26,4 - 33,3	
	5 G 25	razno	36.725	2.380	1.200.0	32,0 - 40,4	
	5 G 35	razno	49.296	2.716	1.680.0	37,0 - 42,0	
	H01N2-D	Gumom oplošten kabel za zavarivanje, normalnog stupnja fleksibilnosti					
		1 x 16	razno	4.897	205	153.6	8,8 - 11,5
	1 x 25	razno	6.619	302	240.0	10,1 - 13,0	
	1 x 35	razno	8.889	420	336.0	11,4 - 14,5	
	1 x 50	razno	12.516	586	480.0	13,2 - 17,0	
	1 x 70	razno	18.253	798	672.0	15,3 - 19,2	
	1 x 95	razno	23.950	1.015	912.0	17,1 - 21,5	
H05RNH2-F	Plosnati gumom oplošten kabel za ukrasnu rasvjetu						
	2 x 2,5	razno	3.683	147	48	5,7 x 13,3	
NSSHöu	Gumom izoliran i oplošten 0,6/1 kV kabel za jača mehanička opterećenja i rudnike						
	3 x 1,5	razno	3.828	195	43.2	11.9	
	4 x 1,5	razno	4.951	226	57.6	12.7	
	5 x 1,5	razno	5.586	264	72.0	13.6	
	3 x 2,5	razno	5.395	257	72.0	13.3	
	4 x 2,5	razno	6.687	343	96.0	15.5	
	5 x 2,5	razno	7.345	402	120.0	16.6	
	4 x 4	razno	10.056	440	153.6	17.1	
	4 x 6	razno	13.025	549	230.4	18.5	
	4 x 10	razno	20.829	855	384.0	22.8	
	4 x 16	razno	30.941	1.224	614.4	26.7	
	4 x 25	razno	43.922	1.802	960.0	31.9	
	4 x 35	razno	59.474	2.230	1.344.0	33.7	

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
NSSHôu	4 x 50	razno	79.925	3.201	1.920.0	40.9
	5 x 4	razno	11.933	521	192.0	18.4
	5 x 6	razno	16.809	694	288.0	20.8
	5 x 10	razno	26.806	1.027	480.0	24.6
SiF Silikonskom gumom izoliran finožični vodič						
	0.5	100	230	8.6	4.8	2.1
	0.75	100	338	11	7.2	2.4
	1	100	411	13.6	9.6	2.4
	1.5	100	514	20	14.4	2.8
	2.5	100	818	32	24.0	3.4
	4	100	1.388	49	38.4	4.2
	6	100	2.046	71	57.6	5.2
	10	100	3.541	124	96.0	7
	16	100	6.040	188	153.6	8
	25	100	9.465	296	240.0	9.9
	35	100	12.978	400	336.0	11.2
SiHF Silikonskom gumom izoliran i oplašten fleksibilni kabel						
	2 x 0,75	razno	1.098	57	14.4	6.4
	3 x 0,75	razno	1.520	66	21.6	6.8
	3 x 1	razno	1.794	78	28.8	7.4
	2 x 1,5	razno	1.657	87	28.8	7.6
	3 x 1,5	razno	2.326	98	43.2	8.0
	4 x 1,5	razno	3.076	122	57.6	8.8
	5 x 1,5	razno	4.266	148	72.0	9.6
	7 x 1,5	razno	5.773	232	100.8	10.9
	3 x 2,5	razno	3.554	152	72.0	9.6
	4 x 2,5	razno	4.744	189	96.0	10.6
	5 x 2,5	razno	6.805	229	120.0	11.6
H07BQ-F Poliuretanom oplašten fleksibilni energetski kabel za gradilišta						
	2 x 1,5	razno	1.956	87.5	28.8	7,6 - 9,8
	3 x 1,5	razno	2.614	107	43.2	8,0 - 10,4
	4 x 1,5	razno	3.105	136	57.6	9,0 - 11,6
	5 x 1,5	razno	3.610	170	72.0	9,8 - 12,7
	3 x 2,5	razno	3.622	159	72.0	9,6 - 12,4
	4 x 2,5	razno	4.721	206	96.0	10,7 - 13,8
	5 x 2,5	razno	6.060	258	120.0	11,9 - 15,3
	3 x 4	razno	5.773	228	115.2	11,3 - 14,5
	5 x 4	razno	9.069	345	192.0	14,1 - 17,9
	5 x 6	razno	12.934	518	288.0	15,7 - 20,0
H07Z-K Bezhalogeni finožični vodič, poboljšanih svojstava za slučaj požara						
	1.5	100	418	20	14.4	2,8 - 3,5
	2.5	100	663	31	24.0	3,4 - 4,3
	4	100	1.005	46	38.4	3,9 - 4,9
	6	100	1.452	65	57.6	4,4 - 5,5
	10	100	2.472	110	96.0	5,7 - 7,1
	16	razno	3.769	170	153.6	6,7 - 8,4
	25	razno	5.802	260	240.0	8,4 - 10,6
	35	razno	8.051	360	336.0	9,7 - 12,1
	50	razno	11.528	515	480.0	11,5 - 14,4
	70	razno	16.090	710	672.0	13,2 - 16,6
	95	razno	21.301	940	912.0	15,2 - 18,8
	120	razno	27.118	1.180	1.152.0	16,7 - 20,9
	150	razno	33.165	1.600	1.440.0	18,6 - 23,3
	185	razno	41.835	2.100	1.776.0	20,6 - 25,8
	240	razno	55.224	3.015	2.304.0	23,5 - 29,4
NHXMH Bezhalogeni instalacijski kabel, 300/500V, poboljšanih svojstava za slučaj požara						
	2 x 1,5	500	1.054	120	28.8	9.0
	3 x 1,5	500	1.309	133	43.2	9.8
	4 x 1,5	500	1.943	157	57.6	10.5
	5 x 1,5	500	2.226	183	72.0	11.5
	7 x 1,5	500	3.705	250	100.8	11
	3 x 2,5	500	1.911	176	72.0	11

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
NHXMH	5 x 2,5	500	3.317	249	120.0	12.5
	3 x 4	razno	3.572	247	115.2	12.5
	3 x 6	razno	5.304	335	172.8	14
	5 x 4	razno	5.857	370	192.0	15.5
	5 x 6	razno	8.357	488	288.0	16.5
	5 x 10	razno	12.761	739	480.0	18
	5 x 16	razno	20.582	1.142	768.0	23
N2XH	Bezhalogeni energetski i signalni 0,6/1 kV kabel, poboljšanih svojstava za slučaj požara					
	1 x 16	razno	4.846	202	154.0	9.1
	1 x 25	razno	7.109	302	240.0	11
	1 x 35	razno	9.570	397	336.0	12
	1 x 50	razno	12.956	523	480.0	13
	1 x 70	razno	17.643	745	672.0	15
	1 x 95	razno	25.073	986	912.0	17
	1 x 120	razno	27.507	1.214	1.152.0	18
	1 x 150	razno	34.430	1.536	1.440.0	21
	1 x 185	razno	42.444	1.888	1.776.0	23
	1 x 240	razno	54.983	2.472	2.304.0	26
	1 x 300	razno	65.828	2.945	2.880.0	28
	2 x 1,5	razno	1.236	120	29.0	9
	2 x 2,5	razno	1.833	154	48.0	10
	3 x 1,5	razno	1.402	135	43.0	9
	3 x 2,5	razno	1.955	181	72.0	10
	3 x 4	razno	3.209	242	115.0	11
	3 x 6	razno	5.003	319	173.0	13
	3 x 10	razno	8.642	464	288.0	14
	4 x 1,5	razno	1.997	163	58.0	10
	4 x 2,5	razno	2.972	214	96.0	11
	4 x 4	razno	4.583	294	154.0	12
	4 x 6	razno	6.587	390	230.0	14
	4 x 10	razno	11.413	586	384.0	16
	4 x 16	razno	17.534	874	614.0	19
	4 x 25	razno	25.643	1.332	960.0	23
	4 x 35	razno	34.974	1.777	1.344.0	26
	4 x 50	razno	46.738	2.343	1.920.0	29
	4 x 70	razno	66.286	3.384	2.688.0	35
	4 x 95	razno	90.922	4.490	3.648.0	39
	4 x 120	razno	113.540	5.558	4.608.0	43
	4 x 150	razno	134.847	6.998	5.760.0	48
	4 x 185	razno	166.236	8.657	7.104.0	53
	4 x 240	razno	212.006	11.385	9.216.0	60
	5 x 1,5	razno	2.159	193	72.0	11
	5 x 2,5	razno	3.194	256	120.0	12
	5 x 4	razno	5.323	352	192.0	13
	5 x 6	razno	7.407	475	288.0	15
	5 x 10	razno	11.775	708	480.0	17
	5 x 16	razno	18.714	1.081	768.0	21
	5 x 25	razno	28.052	1.631	1.200.0	26
	5 x 35	razno	42.185	2.163	1.680.0	29
	7 x 1,5	razno	3.545	300	100.8	15
	10 x 1,5	razno	5.545	360	144	19
	12 x 1,5	razno	6.481	400	172.8	20
	7 x 2,5	razno	7.742	420	168	16
FG16OM16	Bezhalogeni 0,6/1 kV kabel izoliran visokokvalitetnom G16 HEPR smjesom					
	3 G 1,5	razno	1.688	139	43.2	12.5
	3 G 2,5	razno	2.478	185	72.0	13.6
	3 G 4	razno	3.599	246	115.2	14.9
	3 G 6	razno	5.149	313	172.8	16.2
	3 G 10	razno	8.219	503	288.0	18.2
	3 G 16	razno	12.414	609	460.8	20.6
	5 G 1,5	razno	2.595	204	72.0	14.4
	5 G 2,5	razno	3.822	266	120.0	15.6

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
FG16OM16	5 G 4	razno	5.663	361	192.0	17.3
	5 G 6	razno	8.181	471	288.0	18.9
	5 G 10	razno	13.173	756	480.0	21.5
	5 G 16	razno	19.978	1.119	768.0	24.4
NHXH FE180 / E90			Bezhalogeni 0,6/1 kV kabel, s električnom funkcijom od 90 min			
	1 x 25	razno	7.504	347	240.0	11.7
	1 x 35	razno	9.876	449	336.0	12.8
	1 x 50	razno	12.850	589	480.0	14.3
	1 x 70	razno	19.851	810	672.0	16.1
	1 x 95	razno	23.924	1.090	912.0	18.5
	1 x 120	razno	33.571	1.318	1.152.0	19.6
	1 x 150	razno	36.009	1.648	1.440.0	21.8
	1 x 185	razno	47.355	2.029	1.776.0	24
	1 x 240	razno	65.886	2.658	2.304.0	27.2
	2 x 1,5	razno	1.624	178	29.0	11
	3 x 1,5	razno	2.111	200	43.0	11.5
	3 x 2,5	razno	3.081	250	72.0	12.4
	3 x 4	razno	4.572	319	115.0	13.5
	3 x 6	razno	6.447	403	173.0	14.6
	4 x 1,5	razno	3.013	234	58.0	12.4
	4 x 2,5	razno	3.969	296	96.0	13.4
	4 x 4	razno	6.096	381	154.0	14.6
	4 x 6	razno	8.303	490	230.0	15.8
	4 x 10	razno	13.838	695	384.0	17.8
	4 x 16	razno	20.828	1.089	614.0	22.1
	4 x 25	razno	32.804	1.618	960.0	26.3
	4 x 35	razno	42.736	2.083	1.344.0	29
	4 x 50	razno	55.493	2.752	1.920.0	32.8
	4 x 70	razno	78.707	3.804	2.688.0	37.6
	4 x 95	razno	106.889	5.092	3.648.0	43.1
	4 x 120	razno	132.312	6.133	4.608.0	46
	4 x 150	razno	167.825	7.662	5.760.0	51.2
	4 x 185	razno	209.576	9.425	7.104.0	56.5
	4 x 240	razno	273.982	12.334	9.216.0	64.1
	5 x 1,5	razno	3.449	278	72.0	13.4
	5 x 2,5	razno	4.625	353	120.0	14.5
	5 x 4	razno	6.922	456	192.0	15.8
	5 x 6	razno	9.544	589	288.0	17.2
	5 x 10	razno	15.564	832	480.0	19.3
	5 x 16	razno	23.232	1.361	768.0	24.8
	5 x 25	razno	35.428	1.960	1.200.0	28.8
	5 x 35	razno	51.735	2.547	1.680.0	32
	7 x 1,5	razno	4.721	331	101.0	15.8
	7 x 2,5	razno	7.806	426	168.0	17.7
BXO-HFTG			Brodski teškogorivi kabel bez halogena 0,6/1 kV			
	3 x 1,5	razno	2.181	120	43.2	9
	3 x 2,5	razno	3.227	160	72.0	10
H1Z2Z2-K			Kabel za fotonaponske sustave, AC/DC 1500 V			
	1 x 4	500	1.123	58.2	38.4	6.6
	1 x 6	500	1.601	79	57.6	7.4
	1 x 10	500	2.659	128	96.0	8.8
SOLAR MC4 konektor			Konektori za PV kabele			
	4 F 1000 V (4 ... 6mm ²)	100	1.277	9.5		
	4 M 1000 V (4 ... 6mm ²)	100	1.277	11		
	4 F GEN2 1500 V (4 ... 6mm ²)	100	1.329	11.2		
	4 M GEN2 1500 V (4 ... 6mm ²)	100	1.329	13.1		
LiYCY			Elektronički fleksibilni kabel izoliran i oplašten PVC-om, s Cu opletom			
	2 x 0,25	razno	581	28	16.0	4.6
	3 x 0,25	razno	582	34	21.0	4.8
	4 x 0,25	razno	873	40	24.0	5.2
	5 x 0,25	razno	1.016	47	29.0	5.7
	6 x 0,25	razno	1.201	54	32.0	6.3

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
LiYCY	7 x 0,25	razno	1.136	61	37.0	6.3
	8 x 0,25	razno	1.575	66	42.0	6.4
	10 x 0,25	razno	1.902	80	50.0	6.7
	2 x 0,5	100, razno	758	35	23.0	5.2
	3 x 0,5	100, razno	1.053	55	39.0	5.3
	4 x 0,5	100, razno	1.262	61	46.0	5.7
	5 x 0,5	razno	1.584	76	57.0	6.4
	7 x 0,5	razno	2.251	98	80.0	7
	10 x 0,5	razno	2.705	135	100.0	8.8
	12 x 0,5	razno	3.294	157	117.0	9.5
	2 x 0,75	100, razno	766	59	38.0	5.7
	3 x 0,75	100, razno	1.114	66	50.0	5.9
	4 x 0,75	100, razno	1.343	77	58.0	6.5
	5 x 0,75	100, razno	1.746	93	70.0	7
	7 x 0,75	100, razno	2.415	130	100.0	7.8
	8 x 0,75	razno	2.806	145	110.0	8.6
	10 x 0,75	razno	4.699	180	140.0	9.7
	12 x 0,75	razno	4.022	202	154.0	10.2
	2 x 1	100, razno	1.030	65	46.0	6
	3 x 1	100, razno	1.566	80	56.0	6.5
	4 x 1	100, razno	1.732	98	69.0	7.1
	5 x 1	100, razno	2.433	127	89.0	7.8
	7 x 1	razno	3.068	158	118.0	8.5
	8 x 1	razno	3.836	197	130.0	9.4
	10 x 1	razno	5.348	232	145.0	10.8
	12 x 1	razno	5.494	260	168.0	11.2
	2 x 1,5	100, razno	1.423	88	63.0	7.7
	3 x 1,5	100, razno	2.040	100	76.0	7.9
	4 x 1,5	100, razno	2.614	126	108.0	8
	5 x 1,5	razno	3.431	160	129.0	8.8
7 x 1,5	razno	4.270	208	164.0	9.6	
LiYCY-TP Elektronički PVC fleksibilni kabel, s Cu opletom, s uvijenim paricama						
	2 x 2 x 0,5	razno	1.525	93	54.0	7.3
	3 x 2 x 0,5	razno	1.805	129	74.0	8.4
	4 x 2 x 0,5	razno	2.569	146	91.0	9.4
	6 x 2 x 0,5	razno	4.654	198	120.0	11.2
	8 x 2 x 0,5	razno	5.765	259	144.0	11.5
	12 x 2 x 0,5	razno	6.658	354	199.0	15.1
	2 x 2 x 0,75	razno	1.861	106	58.0	9.5
	3 x 2 x 0,75	razno	2.433	140	85.0	9.6
	4 x 2 x 0,75	razno	2.933	179	108.0	10.3
	6 x 2 x 0,75	razno	6.026	246	146.0	12.4
LiHCH Elektronički bezhalogeni fleksibilni kabel, s Cu opletom						
	2 x 0,75	razno	884	59	38.0	5.7
	3 x 0,75	razno	1.125	66	50.0	5.9
	4 x 0,75	razno	1.361	77	58.0	6.5
	5 x 0,75	razno	1.730	93	70.0	7
	7 x 0,75	razno	2.295	130	100.0	7.8
	2 x 1	razno	1.018	65	46.0	6
	3 x 1	razno	1.368	80	56.0	6.5
	4 x 1	razno	1.779	98	69.0	7.1
	5 x 1	razno	2.154	127	89.0	7.8
	7 x 1	razno	2.927	158	118.0	8.5
	2 x 1,5	razno	1.399	88	63.0	7.7
	3 x 1,5	razno	1.859	100	76.0	7.9
	4 x 1,5	razno	2.417	126	108.0	8
	5 x 1,5	razno	2.950	160	129.0	8.8
	7 x 1,5	razno	4.003	208	164.0	9.6
YSLY Signalni fleksibilni kabel izoliran i oplašten PVC-om						
	2 x 0,5	razno	389	35	9.6	4.8
	3 x 0,5	razno	577	41	14.0	5.1
	4 x 0,5	razno	714	49	19.0	5.5

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
YSLY	5 x 0,5	razno	955	60	24.0	6.2
	7 x 0,5	razno	1.172	77	34.0	6.7
	10 x 0,5	razno	1.786	101	48.0	8.5
	12 x 0,5	razno	1.946	125	58.0	9.1
	14 x 0,5	razno	2.675	131	67.0	9.5
	16 x 0,5	razno	2.655	151	77.0	10.3
	21 x 0,5	razno	3.939	215	101.0	11.2
	25 x 0,5	razno	4.376	252	120.0	12.6
	2 x 0,75	razno	505	42	14.0	5.2
	3 x 0,75	razno	675	51	22.0	5.5
	4 x 0,75	razno	893	63	29.0	6.2
	5 x 0,75	razno	1.132	78	36.0	6.7
	6 x 0,75	razno	1.509	85	43.0	7.3
	7 x 0,75	razno	1.587	95	50.0	7.5
	10 x 0,75	razno	2.389	150	72.0	9.6
	12 x 0,75	razno	2.724	165	86.0	9.8
	16 x 0,75	razno	3.695	195	115.0	11.1
	21 x 0,75	razno	5.047	288	151.0	12.5
	25 x 0,75	razno	5.938	330	180.0	14
	34 x 0,75	razno	8.327	435	245.0	16.3
	2 x 1	razno	663	52	19.0	5.6
	3 x 1	razno	890	65	29.0	6.1
	4 x 1	razno	1.165	78	38.0	6.7
	5 x 1	razno	1.469	95	48.0	7.5
	7 x 1	razno	2.025	120	67.0	8.1
	10 x 1	razno	3.036	180	96.0	10.2
	12 x 1	razno	3.361	235	115.0	10.9
	14 x 1	razno	3.730	238	134.0	11.2
	16 x 1	razno	4.802	266	154.0	11.9
	18 x 1	razno	5.387	298	173.0	12.9
	21 x 1	razno	6.542	366	202.0	13.8
	25 x 1	razno	7.254	400	240.0	15.4
	34 x 1	razno	10.691	535	326.0	17.9
	2 x 1,5	razno	904	65	29.0	6.4
	3 x 1,5	razno	1.140	80	43.0	6.8
	4 x 1,5	razno	1.562	102	58.0	7.6
	5 x 1,5	razno	1.942	125	72.0	8.3
	7 x 1,5	razno	2.713	166	101.0	9.2
	10 x 1,5	razno	4.153	243	144.0	11.6
	12 x 1,5	razno	4.895	272	173.0	12.4
	14 x 1,5	razno	5.999	323	202.0	12.7
	16 x 1,5	razno	6.468	361	230.0	13.4
	18 x 1,5	razno	7.640	402	259.0	14.8
	21 x 1,5	razno	8.623	484	302.0	15.6
	25 x 1,5	razno	10.244	555	360.0	17.6
	34 x 1,5	razno	14.269	750	490.0	20.2
	2 x 2,5	razno	1.449	99	48.0	7.6
	3 x 2,5	razno	1.977	128	72.0	8.3
	4 x 2,5	razno	2.602	159	96.0	9
	5 x 2,5	razno	3.203	199	120.0	10.1
	7 x 2,5	razno	4.603	258	168.0	11.2
	10 x 2,5	razno	6.812	310	240.0	13
	12 x 2,5	razno	8.359	361	288.0	15
	18 x 2,5	razno	12.374	519	432.0	18
	3 x 4	razno	3.124	169	115.0	10
	4 x 4	razno	4.233	242	154.0	11
	4 x 6	razno	6.196	340	230.0	13
	4 x 10	razno	10.335	577	384.0	17
	4 x 16	razno	16.935	1.022	614.0	21
	5 x 4	razno	5.412	302	192.0	12.5
	5 x 6	razno	8.112	424	288.0	14
	5 x 10	razno	13.773	717	480.0	18.5

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
YSLY	5 x 16	razno	21.237	1.370	768.0	22.5
	7 x 4	razno	7.403	407	269.0	13.4
	7 x 6	razno	11.093	600	403.0	16
YSLCY Signalni fleksibilni PVC kabel, sa Cu zaslonom						
	2 x 0,75	razno	1.088	59	39.0	6.2
	3 x 0,75	razno	1.284	66	49.0	6.2
	4 x 0,75	razno	1.527	77	57.0	6.7
	5 x 0,75	razno	2.007	93	70.0	7.4
	7 x 0,75	razno	2.507	130	98.0	8.6
	12 x 0,75	razno	3.943	202	151.0	10.7
	16 x 0,75	razno	5.314	275	172.0	12
	25 x 0,75	razno	7.653	415	271.0	15.6
	34 x 0,75	razno	11.355	535	370.0	17.2
	2 x 1	razno	1.205	65	55.0	6.7
	3 x 1	razno	1.558	80	70.0	7
	4 x 1	razno	1.965	98	80.0	7.1
	5 x 1	razno	2.303	127	95.0	8.5
	7 x 1	razno	3.160	158	120.0	9.7
	10 x 1	razno	4.207	232	138.0	12
	12 x 1	razno	4.811	260	186.0	12.4
	14 x 1	razno	6.149	302	198.0	13
	18 x 1	razno	6.583	380	245.0	14.5
	25 x 1	razno	8.493	534	342.0	18
	2 x 1,5	razno	1.428	88	65.0	7.3
	3 x 1,5	razno	2.004	100	90.0	7.7
	4 x 1,5	razno	2.387	126	110.0	8.3
	5 x 1,5	razno	3.086	160	125.0	9.4
	7 x 1,5	razno	3.993	208	159.0	10.7
	12 x 1,5	razno	6.650	338	254.0	13.6
	18 x 1,5	razno	9.192	479	367.0	16.3
	25 x 1,5	razno	13.518	705	492.0	20.3
	2 x 2,5	razno	2.104	130	98.0	9
	3 x 2,5	razno	3.228	167	148.0	9.9
	4 x 2,5	razno	3.660	195	174.0	10.2
	5 x 2,5	razno	4.890	223	200.0	11.6
	7 x 2,5	razno	6.606	344	235.0	13.7
	12 x 2,5	razno	9.398	570	440.0	18.2
	4 x 4	razno	5.793	310	290.0	12.9
	4 x 6	razno	8.147	415	360.0	14.7
	4 x 10	razno	13.019	731	535.0	18.9
	4 x 16	razno	19.256	993	809.0	20.8
	5 x 4	razno	6.515	385	328.0	14.3
	5 x 6	razno	9.040	509	441.0	16.4
BUS kabeli Kabeli za Profibus i KNX sustave						
	BUS PB 1 x 2 x 0,64	razno	2.332	74	30.1	8.0
	BUS EIB / KNX 2 x 2 x 0,8	razno	763	54	21.0	6.6
Kabel za alarme Kabel za alarme						
	4 x 0,22	100	312	21	8.45	3.6
	6 x 0,22	100	315	26	12.67	4.1
	8 x 0,22	100	496	33	16.90	4.5
	12 x 0,22	100	634	45	25.34	5.35
	4 x 0,22 + 2 x 0,5	100	461	35	18.05	4.65
	6 x 0,22 + 2 x 0,75	razno	661	50	27.07	5.35
	12 x 0,22 + 2 x 0,75	razno	1.040	66	38.74	6.3
Kabel za zvučnike Kabel za zvučnike						
	2 x 0,5	100	197	21	9.6	2,4 x 4,8
	2 x 0,75	100	250	29	14.0	2,5 x 5,0
	2 x 1	100	407	32	19.0	2,6 x 5,2
	2 x 1,5	100	532	42	29.0	2,7 x 5,6
	2 x 2,5	100	892	61	48.0	3,6 x 7,4
	2 x 4	100	1.717	110	77.0	4,5 x 9,7
YYSch Telekomunikacijski instalacijski kabel s izolacijom i plaštom od PVC-a						

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
YYSch	2 x 0,6	100	280	12	5.6	3,1 - 3,7
	3 x 0,6	100	390	16	8.4	3,4 - 3,9
	4 x 0,6	100	492	20	11.2	3,5 - 4,1
	5 x 0,6	100	591	26	14.0	4,1 - 4,3
	6 x 0,6	100	691	29	16.8	4,6 - 4,7
	10 x 0,6	100	1.105	54	28.0	5,5 - 6,7
J-Y(St)Y Telekomunikacijski instalacijski PVC kabel, sa zaslonom od Al-folije						
	1 x 2 x 0,6	250	303	30	7.0	5.0
	2 x 2 x 0,6	250	447	40	13.0	5.5
	3 x 2 x 0,6	250	687	50	18.0	6.3
	4 x 2 x 0,6	100, 250	767	60	24.0	6.8
	5 x 2 x 0,6	100, 250	1.023	70	30.0	7.2
	6 x 2 x 0,6	100	1.190	80	35.0	7.5
	10 x 2 x 0,6	razno	1.877	110	58.0	9.0
	20 x 2 x 0,6	razno	3.505	190	116.0	11.0
	30 x 2 x 0,6	razno	5.616	280	172.0	13.0
	50 x 2 x 0,6	razno	8.565	440	286.0	17.0
	100 x 2 x 0,6	razno	17.133	850	568.0	23.0
	1 x 2 x 0,8	250	429	40	11.0	6.0
	2 x 2 x 0,8	100, 250, 500	632	60	21.0	7.0
	3 x 2 x 0,8	100, 250	1.013	80	31.0	8.5
	4 x 2 x 0,8	100, 250	1.257	100	41.0	9.0
	5 x 2 x 0,8	100, 250	1.716	120	52.0	9.5
	6 x 2 x 0,8	100	2.023	140	62.0	10.5
	10 x 2 x 0,8	razno	3.241	210	102.0	13.0
	20 x 2 x 0,8	razno	6.094	380	204.0	16.5
	30 x 2 x 0,8	razno	9.439	550	304.0	20.0
JB-Y(St)Y Vatrodojavni instalacijski PVC kabel, sa zaslonom od Al-folije						
	1 x 2 x 0,8	100, 500	406	40	11.0	6.0
	2 x 2 x 0,8	100, 500	625	60	21.0	7.0
	4 x 2 x 0,8	500, razno	1.346	100	41.0	9.0
J-H(St)Y Bezhalogeni telekomunikacijski kabel, poboljšanih svojstava za slučaj požara						
	2 x 2 x 0,8	razno	824	69	25.0	7.0
	2 x 2 x 0,8 (crveni)	razno	823	69	25.0	7.0
	4 x 2 x 0,8	razno	1.612	136	45.0	9.0
	4 x 2 x 0,8 (crveni)	razno	1.612	136	45.0	9.0
JE-H(St)H FE180 / E30-E90 Bezhalogeni kabel za industrijsku elektroniku, s funkcijom od 30 i 90 minuta						
	1 x 2 x 0,8	razno	855	40	15.0	5.5
	2 x 2 x 0,8	razno	1.211	56	25.0	6.6
	4 x 2 x 0,8	razno	2.402	96	45.0	8.7
TK 59-50 xDSL Telekom, distributivni kabel, vanjski, niskofrekventni za širokopolasne usluge						
	2 x 2 x 0,5	razno	847	55	7.0	7.5
	6 x 2 x 0,5	razno	1.592	95	20.8	9.8
	10 x 2 x 0,5	razno	2.513	125	34.8	11.0
	20 x 2 x 0,5	razno	4.508	200	69.5	12.9
	50 x 2 x 0,5	razno	9.824	270	173.8	17.8
TK 59U-50 xDSL Telekom, samonosivi distributivni kabel, niskofrekventni za širokopolasne usluge						
	6 x 2 x 0,5	razno	2.268	130	20.8	9,4 x 16,7
F-2YA2Y Telekomunikacijski kabel za vanjsku uporabu, podzemni						
	2 x 2 x 0,8	razno	965	55	25	7.3
	6 x 2 x 0,8	razno	2.355	115	62	10.4
	10 x 2 x 0,8	razno	3.631	170	102	12.0
Koax 75 Ohm Koaksijalni kabel 75 Ohm						
	CATV 1,13/4,8 AF Tri-Shld	100, 500	719	50	18.5	6.8
	CATV 1,13/4,8 AF Tri-Shld LSOH	100	823	50	18.5	6.8
	RG 6	100	248	41	15.0	6.8
	RG 11	razno	1.593	135	62.6	10.1
	RG 59 B/U	100	484	54	24.7	6.15
	KOAX6 CT 15 A PE podzemni	razno	2.557	102	56.0	10.1
Koax 50 Ohm Koaksijalni kabel 50 Ohm						
	RG 58 C/U 50 Ohm	100	704	37	20	4.95
	RG 213 U 50 Ohm	razno	3.067	157	87	10.3

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
Cat.5e 200 Mhz		LAN kabel kategorije 5e, do 200 MHz				
	U/UTP PVC	305, 500	482	35	17.5	4,9 - 5,1
	U/UTP LSOH	500	562	36	17.5	4,9 - 5,1
	F/UTP PVC	500	632	36	19.8	5,9 - 6,6
	F/UTP LSOH	500	721	37	19.8	5,9 - 6,6
	SF/UTP LSOH	500	1.068	47	27	6,4 - 6,6
	U/UTP PE outdoor	500	748	39	12	7.5
	F/UTP PE outdoor	500	932	39	12	7.5
	U/UTP flex	500	752	26	11	5.2
	F/UTP flex	500	898	26	12	5.4
Cat. 6 350 Mhz		LAN kabel kategorije 6, do 350 MHz				
	U/UTP PVC	305, 500	603	39	20.5	6,2 - 6,8
	U/UTP LSOH	500	638	40	20.5	6,2 - 6,8
	U/FTP PVC	500	846	41	24.0	6,5 - 7,6
	U/FTP LSOH	500	871	44	24.0	6,5 - 7,6
	S/FTP LSOH	500	1.095	49	34.0	7,4 - 8,2
	U/UTP PE outdoor	500	864	39	20.5	7.5
Cat. 6A 500 Mhz		LAN kabel kategorije 6A, do 500 MHz				
	U/FTP LSOH	500	966	44	24.0	6.5
Cat. 7 800 Mhz		LAN kabel kategorije 7, do 800 MHz				
	S/FTP LSOH	500	1.059	55	26.0	7,3 - 8,0
	S/FTP PE outdoor	500	1.599	62	26.0	8.3
Multimode		Svjetlovodni Unitube kabel sa MM nitima, s ojačanjem i zaštitom od glodavaca				
	4 G 50 / 125 OM2	razno	825	40		5.8
	8 G 50 / 125 OM2	razno	1.168	40		5.8
	12 G 50 / 125 OM2	razno	1.508	40		5.8
	24 G 50 / 125 OM2	razno	2.764	45		6.9
	4 G 50 / 125 OM3	razno	1.234	40		5.8
	8 G 50 / 125 OM3	razno	2.419	40		5.8
Singlemode		Svjetlovodni kabel s SM nitima, Unitube / Stranded loose tube, za vanjsku upotrebu				
	1 x 4E9 / 125 4 niti G.657a	razno	779	7		2.5
	3 x 4E9 / 125 12 niti G.652d	razno	768	75		9.6
	6 x 4E9 / 125 24 niti G.652d	razno	996	78		9.6
	6 x 8E9 / 125 48 niti G.652d	razno	1.554	97		11.3
	8 x 12E9 / 125 96 niti G.652d	razno	4.272	97		11.8