

Provjerite naše nove web stranice !

www.tim-kabel.hr

Tehnička pomoć:

info@tim-kabel.hr

Kontakti prodaja:

ZG: 01 5555 900, **ST:** 021 374 444, **OS:** 031 297 607

PVC-om izolirani instalacijski kabe i vodiči		str
H07V-U	P	▼ 1
H07V-R	P/M	▼ 1
H05V-K	P/F	▼ 1
H07V-K	P/F	▼ 1
H07V2-K	P/FT	▼ 1
(N)YM	PP-Y	▼ 1
NYiFY	PP/R	▼ 2
H03VH-H	P/L	▼ 2
H03VV-F	PP/L	▼ 2
H05VV-F	PP/J	▼ 2

EPR, PUR i silikonom izolirani kabe i vodiči		str
H05RR-F	GG/J	▼ 5, 6
H07RN-F	GN/J	▼ 6
H01N2-D		▼ 6
H05RNH2-F		▼ 6
NSSHöu	EPN-50	▼ 6, 7
SiF		▼ 7
SiHF		▼ 7
H07BQ-F		▼ 7

Upravljački i kabe i za elektroniku		str
LiYCY		▼ 10
LiYCY-TP		▼ 10
LiHCH		11
YSLY		▼ 11, 12
YSLCY		▼ 12, 13
BUS kabe i		▼ 13
Kabe i za alarme		▼ 13
Kabe i za zvučnike		▼ 13

LAN kabe i		str
Cat.5e		▼ 14
Cat 6, Cat 6A		▼ 14
Cat 7		▼ 14

Energetski kabe i 1 - 36 kV		str
E-YY	PP00	▼ 2, 3
FG16(O)R16		▼ 3, 4
NYCY	PP40	▼ 4
NYCWX	PP40	▼ 4, 5
NA2XY	XP00-A	▼ 5
NFA2X	X00-A	▼ 5
NA2XS(F)2Y 20 kV	XHE 49-A	▼ 5
EAXeCWB 36 kV	XHE 49-A	5
Bakreno uže		▼ 5
Fe/Zn traka		5

Kabe i bez halogena		str
H07Z-K		▼ 7, 8
NHXMH		▼ 8
N2XH		▼ 8, 9
FG16OM16		9
NHXH E90		▼ 9
BXO-HFTG	MPRX LKM-HF	▼ 10
H1Z2Z2-K	Solarni kabe i	▼ 10
Konektor MC4 SOLAR		▼ 10

Telekomunikacijski i Koaksijalni kabe i		str
YYSch		▼ 13
J-Y(St)Y	TI44	▼ 13
JB-Y(St)Y		▼ 13
J-H(St)Y		▼ 13
JE-H(St)H E30-E90		▼ 14
TK59(U) xDSL		14
F-2YA2Y	TK33	▼ 14
Koax 75 Ω		▼ 14
Koax 50 Ω		▼ 14

Svjetlovodni kabe i		str
Multimode		▼ 14
Singlemode		▼ 14

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
H07V-U PVC-om izolirani vodič - jednožični (punji)						
	1.5	100	319	20	14.4	2,6 - 3,2
	2.5	100	514	31	24.0	3,2 - 3,9
	4	100	975	46	38.4	3,6 - 4,4
	6	100	1.432	65	57.6	4,1 - 5,0
	10	100	2.208	110	96.0	5,3 - 6,4
H07V-R PVC-om izolirani vodič - višezžični						
	10	100	2.382	112	96	5,6 - 6,7
	16	razno	4.068	170	153.6	6,4 - 7,8
	25	razno	6.477	260	240.0	8,1 - 9,7
	35	razno	8.790	340	336.0	9,0 - 10,9
H05V-K PVC-om izolirani vodič - finožični						
	0.5	100	148	10	4.8	2,1 - 2,5
	0.75	100	198	12	7.2	2,2 - 2,7
	1	100	256	14	9.6	2,4 - 2,8
H07V-K PVC-om izolirani vodič - finožični						
	1.5	100	328	20	14.4	2,8 - 3,4
	2.5	100	535	31	24.0	3,4 - 4,1
	4	100	850	46	38.4	3,9 - 4,8
	6	100	1.226	65	57.6	4,4 - 5,3
	10	100	2.057	110	96.0	5,7 - 6,8
	16	100	3.255	170	153.6	6,7 - 8,1
	25	100, razno	5.185	260	240.0	8,4 - 10,2
	35	razno	7.243	360	336.0	9,7 - 11,7
	50	razno	10.958	515	480.0	11,5 - 13,9
	70	razno	15.068	710	672.0	13,2 - 16,0
	95	razno	20.137	940	912.0	15,1 - 18,2
	120	razno	25.654	1.180	1.152.0	16,7 - 20,2
	150	razno	32.532	1.600	1.440.0	18,6 - 22,5
	185	razno	38.389	2.100	1.776.0	20,6 - 24,9
	240	razno	51.821	3.015	2.304.0	23,5 - 28,4
H07V2-K PVC-om izolirani vodič - finožični, s povećanom otpornošću na toplinu						
	150	razno	43.107	1.534	1.440.0	19,2 - 21,2
(N)YM PVC-om izoliran i oplašten instalacijski kabel						
	2 x 1,5	100	869	115	28.8	8,4 - 9,8
	3 x 1,5	50, 100	1.028	135	43.2	8,8 - 10,5
	3 x 1,5	500	1.062	135	43.2	8,8 - 10,5
	4 x 1,5	100	1.425	160	57.6	9,5 - 11,0
	4 x 1,5	500	1.495	160	57.6	9,5 - 11,0
	5 x 1,5	50, 100	1.667	190	72.0	9,9 - 12,0
	5 x 1,5	500	1.760	190	72.0	9,9 - 12,0
	7 x 1,5	100, 500	2.784	235	100.8	11,0 - 13,0
	3 x 2,5	50, 100	1.612	190	72.0	10,0 - 11,5
	3 x 2,5	500	1.685	190	72.0	10,0 - 11,5
	4 x 2,5	100	2.257	230	96.0	11,0 - 12,5
	4 x 2,5	500	2.612	230	96.0	11,0 - 12,5
	5 x 2,5	50, 100	2.606	270	120.0	11,5 - 13,5
	5 x 2,5	500	2.722	270	120.0	11,5 - 13,5
	3 x 4	razno	3.054	265	115.2	11,5 - 13,0
	3 x 6	razno	4.623	315	172.8	12,0 - 15,0
	4 x 4	razno	4.284	330	153.6	12,5 - 14,5
	4 x 6	razno	6.255	460	230.4	14,5 - 16,5
	4 x 10	razno	10.879	690	384.0	16,5 - 19,0
	5 x 6	100, razno	6.450	540	288.0	15,5 - 18,0
	5 x 4	100, razno	4.490	410	192.0	14,0 - 16,5
	5 x 10	razno	11.350	870	480.0	18,5 - 21,5
NYiFY PVC-om izoliran i oplašten instalacijski plosnati kabel						
	3 x 1,5	100	1.281	102	43.2	15,5 x 4,0

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
NYiFY	3 x 2,5	100	2.007	152	72.0	18,2 x 4,5
H03VH-H PVC-om izolirani fleksibilni plosnati kabel						
	2 x 0,75	100	433	26	14.4	2,8 x 5,7
H03VV-F PVC-om izoliran i oplošten laki finožični kabel						
	2 x 0,75	100, 500	435	48	14.4	4,9 - 6,3
	3 G 0,75	100, 500	611	57	21.6	5,2 - 6,7
	4 G 0,75	100	815	70	28.8	5,7 - 7,3
	5 G 0,75	100	1.022	87	36.0	7,0 - 7,4
H05VV-F PVC-om izoliran i oplošten finožični kabel						
	2 x 1	100	609	65	19.2	5,9 - 7,5
	3 G 1	100	865	80	28.8	6,3 - 8,0
	4 G 1	100	1.234	92	38.4	7,1 - 9,0
	5 G 1	100	1.527	113	48.0	7,8 - 9,8
	7 G 1	100	2.184	136	67.2	8,8 - 9,5
	2 x 1,5	100	809	90	28.8	6,8 - 8,6
	3 G 1,5	100, razno	1.096	115	43.2	7,4 - 9,4
	4 G 1,5	100	1.587	145	57.6	8,4 - 10,5
	5 G 1,5	100, razno	1.831	175	72.0	9,3 - 11,6
	7 G 1,5	100	2.956	195	100.8	10,6
	2 x 2,5	100	1.464	115	48.0	8,4 - 10,6
	3 G 2,5	100, razno	1.815	175	72.0	9,2 - 11,4
	4 G 2,5	100	2.599	210	96.0	10,1 - 12,5
	5 G 2,5	100	2.935	260	120.0	11,2 - 13,9
	5 G 4	razno	5.359	363	192.0	13,0 - 16,1
	5 G 6	razno	7.494	583	288.0	16,7
E-YY-O Energetski 0,6/1 kV kabel izoliran i oplošten PVC-om bez zaštitnog vodiča						
	1 x 16	razno	4.416	240	153.6	10,0 - 13,0
	1 x 25	razno	6.687	350	240.0	12,0 - 15,0
	1 x 35	razno	9.069	460	336.0	13,0 - 16,0
	1 x 50	razno	12.305	600	480.0	14,0 - 17,0
	1 x 70	razno	16.817	800	672.0	16,0 - 19,0
	1 x 95	razno	23.286	1.100	912.0	18,0 - 21,0
	1 x 120	razno	29.617	1.350	1.152.0	19,0 - 22,0
	1 x 150	razno	35.313	1.650	1.440.0	21,0 - 25,0
	1 x 185	razno	45.191	2.000	1.776.0	23,0 - 27,0
	1 x 240	razno	59.773	2.600	2.304.0	26,0 - 30,0
	1 x 300	razno	75.144	3.200	2.880.0	28,0 - 32,0
	2 x 1,5	razno	1.103	190	28.8	11,0 - 13,0
	2 x 2,5	razno	1.536	230	48.0	12,0 - 14,0
	2 x 4	razno	2.688	310	76.8	13,0 - 15,0
	2 x 6	razno	3.987	380	115.2	14,0 - 16,0
E-YY-J Energetski 0,6/1 kV kabel izoliran i oplošten PVC-om, sa zaštitnim vodičem						
	3 x 1,5	100, razno	1.174	190	43.2	11,0 - 14,0
	3 x 2,5	100, razno	1.758	240	72.0	12,0 - 15,0
	3 x 4	razno	3.291	330	115.2	14,0 - 17,0
	3 x 6	razno	4.741	420	172.8	15,0 - 18,0
	3 x 10	razno	8.356	580	288.0	17,0 - 20,0
	4 x 1,5	razno	1.697	220	57.6	12,0 - 16,0
	4 x 2,5	razno	2.499	290	96.0	13,0 - 17,0
	4 x 4	razno	4.099	400	153.6	15,0 - 19,0
	4 x 6	razno	6.221	510	230.4	16,0 - 20,0
	4 x 10 RM	razno	9.574	720	384.0	18,0 - 22,0
	4 x 16	razno	14.814	1.050	614.4	21,0 - 25,0
	4 x 25	razno	23.376	1.600	960.0	25,0 - 32,0
	4 x 35	razno	32.123	1.750	1.344.0	27,0 - 34,0
	4 x 50	razno	41.669	2.300	1.920.0	29,0 - 36,0
	4 x 70	razno	59.605	3.100	2.688.0	33,0 - 40,0
	4 x 95	razno	82.664	4.200	3.648.0	38,0 - 45,0
	4 x 120	razno	103.942	5.200	4.608.0	41,0 - 49,0
	4 x 150	razno	128.852	6.400	5.760.0	46,0 - 54,0
	4 x 185	razno	156.899	8.050	7.104.0	51,0 - 59,0
	4 x 240	razno	208.318	11.000	9.216.0	57,0 - 65,0

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)	
E-YY-J	5 x 1,5	razno	1.889	270	72.0	13,0 - 16,0	
	5 x 2,5	razno	2.897	350	120.0	14,0 - 17,0	
	5 x 4	razno	4.849	480	192.0	15,0 - 18,0	
	5 x 6	razno	7.000	610	288.0	18,0 - 21,0	
	5 x 10 RM	razno	11.236	880	480.0	19,0 - 22,0	
	5 x 16	razno	17.416	1.250	768.0	22,0 - 25,0	
	5 x 25	razno	28.901	1.950	1.200.0	27,0 - 33,0	
	5 x 35	razno	38.723	2.400	1.680.0	33,0 - 40,0	
	5 x 50	razno	57.629	3.500	2.400.0	39,0 - 45,0	
	5 x 70	razno	81.647	4.450	3.360.0	41,0 - 47,0	
	5 x 95	razno	112.723	6.134	4.560.0	46,0 - 52,0	
E-YY-JZ Signalni 0,6/1 kV kabel izoliran i oplašten PVC-om							
E-YY-JZ	7 x 1,5	razno	3.174	300	100.8	14,1 - 17	
	10 x 1,5	razno	5.394	360	144.0	17,2 - 21	
	12 x 1,5	razno	6.043	400	172.8	17,7 - 22	
	14 x 1,5	razno	7.574	450	201.6	18,5 - 23	
	16 x 1,5	razno	7.996	500	230.4	19,4 - 24	
	19 x 1,5	razno	10.071	560	273.6	20,3 - 25	
	24 x 1,5	razno	10.620	700	345.6	22,9 - 28	
	7 x 2,5	razno	5.283	420	168.0	15,9 - 18	
	10 x 2,5	razno	8.608	500	240.0	19,6 - 22	
	12 x 2,5	razno	9.645	560	288.0	20,2 - 23	
	14 x 2,5	razno	11.923	630	336.0	21,0 - 24	
	16 x 2,5	razno	14.131	710	384.0	22,0 - 25	
	19 x 2,5	razno	15.619	830	456.0	23,0 - 26	
	24 x 2,5	razno	18.666	1.050	576.0	26,9 - 30	
	FG16R16 Energetski fleksibilni 0,6/1 kV kabel izoliran HEPR gumom i oplašten PVC-om R16 kvalitete						
FG16R16	1 x 25	razno	6.784	301	240.0	11.4	
	1 x 35	razno	8.436	396	336.0	14.6	
	1 x 50	razno	11.670	556	480.0	16.4	
	1 x 70	razno	16.152	761	672.0	17.3	
	1 x 95	razno	20.875	991	912.0	20.4	
	1 x 120	razno	27.700	1.219	1.152.0	22.4	
	1 x 150	razno	33.582	1.517	1.440.0	24.8	
	1 x 185	razno	41.961	1.821	1.776.0	27.2	
	1 x 240	razno	53.579	2.366	2.304.0	30.4	
	1 x 300	razno	68.923	2.947	2.880.0	33.0	
	1 x 400	razno	102.419	3.870	3.840.0	37.7	
	FG16OR16 Energetski fleksibilni 0,6/1 kV kabel izoliran HEPR gumom i oplašten PVC-om R16 kvalitete						
	FG16OR16	2 x 1,5	razno	1.581	125	28.8	12.0
2 x 2,5		razno	2.179	151	48.0	13.0	
2 x 4		razno	3.067	207	76.8	14.2	
2 x 6		razno	4.276	256	115.2	15.4	
2 x 10		razno	6.837	395	192.0	17.3	
3 G 1,5		razno	1.624	139	43.2	12.5	
3 G 2,5		razno	2.393	185	72.0	13.6	
3 G 4		razno	3.457	246	115.2	14.9	
3 G 6		razno	4.941	313	172.8	16.2	
3 G 10		razno	8.209	503	288.0	18.2	
3 x 35 + 1 G 25		razno	33.385	1611	1.248.0	29.2	
3 x 50 + 1 G 25		razno	45.046	2.142	1.680.0	32.4	
3 x 70 + 1 G 35		razno	60.842	3.037	2.352.0	37.0	
3 x 95 + 1 G 50		razno	82.251	4.047	3.216.0	42.0	
3 x 120 + 1 G 70		razno	112.128	5.327	4.128.0	46.9	
3 x 150 + 1 G 95		razno	154.403	6.635	5.232.0	52.5	
4 G 1,5		razno	2.285	171	57.6	13.4	
4 G 2,5		razno	3.022	222	96.0	14.6	
4 G 4		razno	4.795	297	153.6	16.0	
4 G 6		razno	7.161	392	230.4	17.5	
4 G 10		razno	10.967	611	384.0	19.8	
4 G 16		razno	16.240	886	614.4	22.4	
4 G 25		razno	25.028	1.255	960.0	26.8	

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
FG16OR16	4 G 35	razno	36.622	1.750	1.344.0	30.5
	4 G 50	razno	52.070	2.530	1.920.0	34.1
	4 G 70	razno	73.482	3.600	2.688.0	36.6
	4 G 95	razno	97.361	4.380	3.648.0	41.5
	4 G 120	razno	123.724	5.585	4.608.0	45.8
	4 G 150	razno	155.009	6.920	5.760.0	52.1
	5 G 1,5	razno	2.596	204	72.0	14.4
	5 G 2,5	razno	3.597	266	120.0	15.6
	5 G 4	razno	5.445	361	192.0	17.3
	5 G 6	razno	7.639	471	288.0	18.9
	5 G 10	razno	12.968	756	480.0	21.5
	5 G 16	razno	19.351	1.119	768.0	24.4
	5 G 25	razno	29.943	1.597	1.200.0	29.3
	5 G 35	razno	41.392	2.140	1.680.0	32.8
	5 G 50	razno	62.935	3.030	2.400.0	38.2
	7 G 1,5	razno	4.046	247	100.8	15.4
	7 G 2,5	razno	5.863	381	168.0	16.8
	12 G 1,5	razno	7.003	380	172.8	19.3
NYCY Energetski i signalni 0,6/1 kV kabel izoliran i oplašten PVC-om, s koncentričnim vodičem						
	2 x 1,5 / 1,5	razno	2.475	200	52.0	12 - 13
	3 x 1,5 / 1,5	razno	2.875	220	66.0	13 - 17
	4 x 1,5 / 1,5	razno	3.267	250	81.0	14 - 18
	5 x 1,5 / 1,5	razno	3.719	330	95.0	15 - 16
	7 x 1,5 / 2,5	razno	4.892	350	133.0	14 - 19
	12 x 1,5 / 2,5	razno	7.389	470	205.0	19 - 24
	16 x 1,5 / 4	razno	10.192	620	276.0	20
	19 x 1,5 / 4	razno	12.605	660	320.0	22 - 28
	24 x 1,5 / 6	razno	15.033	850	413.0	25 - 31
	30 x 1,5 / 6	razno	17.984	1.020	499.0	32
	2 x 2,5 / 2,5	razno	3.059	260	80.0	13,3 - 14
	3 x 2,5 / 2,5	razno	3.633	280	104.0	14 - 17
	4 x 2,5 / 2,5	razno	4.278	340	128.0	15 - 19
	5 x 2,5 / 2,5	razno	5.178	400	152.0	16 - 17
	7 x 2,5 / 2,5	razno	6.575	450	200.0	17 - 21
	10 x 2,5 / 4	razno	10.264	600	286.0	20 - 25
	12 x 2,5 / 4	razno	10.055	660	334.0	20 - 25
	16 x 2,5 / 6	razno	15.395	800	451.0	22.5
	19 x 2,5 / 6	razno	17.380	940	523.0	23 - 29
	21 x 2,5 / 6	razno	17.067	1.100	571.0	26
	24 x 2,5 / 6	razno	22.159	1.150	696.0	27 - 33
	2 x 4 / 4	razno	4.481	350	123.0	15,3 - 16,0
	3 x 4 / 4	razno	6.235	390	161.0	15 - 18
	4 x 4 / 4	razno	5.917	460	200.0	16 - 20
	5 x 4 / 4	razno	8.351	550	238.0	19
	2 x 6 / 6	razno	6.109	430	182.0	16,1 - 17,5
	3 x 6 / 6	razno	8.811	500	240.0	16 - 20
	4 x 6 / 6	razno	9.082	580	297.0	17 - 21
	5 x 6 / 6	razno	11.821	700	355.0	20 - 22
	4 x 10 / 10	razno	16.293	765	504.0	19 - 23
	4 x 16 / 16	razno	22.956	1.060	796.0	21 - 25
NYCWY Energetski 0,6/1 kV PVC kabel, s valovitim koncentričnim Cu vodičem						
	4 x 10 / 10	razno	14.609	870	504	19 - 23
	4 x 16 / 16	razno	22.516	1.250	796	21 - 25
	4 x 25 / 16	razno	31.772	1.800	1.142	25 - 32
	4 x 35 / 16	razno	41.356	2.050	1.526	26 - 33
	4 x 50 / 25	razno	56.157	2.700	2.203	29 - 36
	4 x 70 / 35	razno	79.717	3.750	3.082	34 - 41
	4 x 95 / 50	razno	108.605	5.000	4.208	42 - 47
	4 x 120 / 70	razno	138.038	6.300	5.388	43 - 50
NA2XY Energetski 0,6/1 kV kabel izoliran PVC-om i oplašten XLPE-om, s Al vodičima						
	1 x 70	razno	2.694	383	203.0	16 - 19
	1 x 95	razno	3.569	490	275.5	18 - 21

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
NA2XY	1 x 120	razno	4.318	575	348.0	19 - 22
	1 x 150	razno	5.299	695	435.0	21 - 25
	1 x 185	razno	6.429	845	536.5	23 - 27
	1 x 240	razno	8.278	1.100	696.0	26 - 30
	4 x 16	razno	3.092	750	185.6	21 - 25
	4 x 25	razno	4.413	950	290.0	25 - 32
	4 x 35	razno	5.974	1.141	406.0	27 - 34
	4 x 50	razno	7.759	1.242	580.0	29 - 36
	4 x 70	razno	10.684	1.631	812.0	33 - 40
	4 x 95	razno	13.252	2.063	1.102.0	38 - 45
	4 x 120	razno	16.790	2.538	1.392.0	41 - 49
	4 x 150	razno	19.675	3.090	1.740.0	46 - 54
	4 x 185	razno	24.915	3.838	2.146.0	51 - 59
	4 x 240	razno	32.275	4.863	2.784.0	57 - 65
	NFA2X Samonosivi kabelski snop 0,6/1kV s XLPE-izolacijom					
	2 x 16	razno	1.148	137	82.8	15
	4 x 16	razno	2.320	270	186.0	18
NA2XS(F)2Y 12/20 kV Sredjenaponski 12/20 kV kabel XLPE / PE, Aluminijski vodič , uzdužno vodonepropustan						
	1 x 70 / 16		12.224	907	203,0 / 153,6	31
	1 x 95 / 16		13.321	1.304	275,5 / 153,6	33
	1 x 120 / 16		15.672	1.139	348,0 / 153,6	34
	1 x 150 / 25		17.512	1.251	435,0 / 240,0	36
	1 x 185 / 25		20.101	1.450	536,5 / 240,0	37
	1 x 240 / 25		21.723	1.698	696,0 / 240,0	40
	1 x 300 / 25		25.116	1.917	870,0 / 240,0	42
	1 x 400 / 35		30.820	2.336	1.160,0 / 336,0	45
EAXeCWB 20,8/36 kV Sredjenaponski 20,8/36 kV kabel XLPE / PE, Aluminijski vodič , uzdužno vodonepropustan						
	1 x 150 / 25		21.686	1.750	435,0 / 240,0	44
	1 x 185 / 25		23.996	1.950	536,5 / 240,0	46
	1 x 240 / 25		26.163	2.200	696,0 / 240,0	48
Bakreno uže Goło bakreno uže klase 3						
	16	razno	3.325	142	142.0	5.1
	25	razno	5.510	217	217.0	6.3
	35	razno	7.309	308	308.0	7.5
	50	razno	9.238	443	443.0	9.0
	70	razno	14.747	590	590.0	10.5
	95	razno	20.978	836	836.0	12.5
Fe/Zn traka Pocičana traka za gromobranske i slične sustave						
	20 x 3	48 - 52	3.018			20 x 3
	25 x 4	48 - 52	2.916			25 x 4
	30 x 4	48 - 52	3.018			30 x 4
	40 x 4	48 - 52	3.018			40 x 4
	spojnica 60x60/3		2.222			60 x 60 x 3
	spojnica 80x80/3		2.980			80 x 80 x 3
H05RR-F Lakom EPR gumom oplašten i izoliran fleksibilni kabel						
	2 x 0,75	100	832	63	14.4	5,7 - 8,2
	3 G 0,75	100	1.088	78	21.6	6,2 - 8,8
	2 x 1	100	1.020	73	19.2	6,1 - 8,8
	2 x 1,5	100	1.326	103	28.8	7,6 - 10,5
	3 G 1,5	100	1.587	125	43.2	8,0 - 11,0
	4 G 1,5	100	2.141	154	57.6	9,0 - 12,5
	5 G 1,5	100	2.674	182	72.0	9,8 - 13,5
	2 G 2,5	100	2.075	146	48.0	9,0 - 12,5
	3 G 2,5	100	2.385	177	72.0	9,6 - 13,0
	4 G 2,5	100	3.301	222	96.0	10,7 - 14,0
	5 G 2,5	100	3.929	269	120.0	11,9 - 15,5
H07RN-F Teškom gumom oplašten i gumom izoliran fleksibilni kabel						
	1 x 10	razno	3.385	204	96	9,5 - 11,9
	1 x 16	razno	4.844	286	153.6	10,8 - 13,4
	1 x 25	razno	7.168	390	240	12,7 - 15,8
	1 x 35	razno	9.810	523	336	14,3 - 17,9
	1 x 50	razno	13.934	699	480	16,5 - 20,6

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
H07RN-F	1 x 70	razno	19.097	950	672	18,6 - 23,3
	1 x 95	razno	25.240	1202	912	20,8 - 26,0
	1 x 120	razno	32.098	1524	1152	22,8 - 28,6
	1 x 150	razno	39.810	1839	1440	25,2 - 31,4
	1 x 185	razno	47.497	2184	1776	27,6 - 34,4
	1 x 240	razno	61.688	2840	2304	30,6 - 38,3
	1 x 300	razno	78.444	3413	2880	33,5 - 41,9
	2 x 1,5	razno	1.518	136	28.8	8,5 - 11,0
	3 G 1,5	100, razno	1.738	162	43.2	9,2 - 11,9
	4 G 1,5	100, razno	2.362	197	57.6	10,2 - 13,1
	5 G 1,5	100, razno	3.186	234	72.0	11,2 - 14,4
	7 G 1,5	razno	4.925	335	100.8	14,0 - 15,7
	12 G 1,5	razno	7.682	560	172.8	17,6 - 22,4
	19 G 1,5	razno	12.242	795	273.6	22,5 - 26,6
	24 G 1,5	razno	15.225	1.000	345.6	24,3 - 30,7
	2 G 2,5	razno	2.269	190	48.0	10,2 - 13,1
	3 G 2,5	100, razno	2.561	229	72.0	10,9 - 14,0
	4 G 2,5	100, razno	3.481	279	96.0	12,1 - 15,5
	5 G 2,5	100, razno	4.163	348	120.0	13,3 - 17,0
	7 G 2,5	razno	7.453	520	168.0	16,5 - 18,2
	12 G 2,5	razno	11.483	760	288.0	18,5 - 22,5
	19 G 2,5	razno	19.409	1.075	456.0	24,6 - 31,0
	24 G 2,5	razno	22.859	1.390	576.0	28,8 - 36,4
	3 G 4	razno	4.107	329	115.2	12,7 - 16,2
	3 G 6	razno	6.168	452	172.8	14,1 - 18,0
	3 G 10	razno	10.608	776	288.0	19,1 - 24,2
	4 G 4	razno	5.066	402	153.6	14,0 - 17,9
	4 G 6	razno	7.077	561	230.4	15,7 - 20,0
	4 G 10	razno	12.470	935	384.0	20,9 - 26,5
	4 G 16	razno	17.751	1.286	614.4	23,8 - 30,1
	4 G 25	razno	29.234	1.692	960.0	28,9 - 36,6
	4 G 35	razno	38.696	2.266	1.344.0	32,5 - 41,1
	4 G 50	razno	56.200	3.021	1.920.0	37,7 - 47,5
	4 G 70	razno	78.942	4.121	2.688.0	42,7 - 54,0
	4 G 95	razno	101.505	5.361	3.648.0	48,4 - 61,0
5 G 4	razno	6.149	470	192.0	15,6 - 19,9	
5 G 6	razno	8.403	620	288.0	17,5 - 22,2	
5 G 10	razno	15.722	1.155	480.0	22,9 - 29,1	
5 G 16	razno	22.934	1.460	768.0	26,4 - 33,3	
5 G 25	razno	38.312	2.380	1.200.0	32,0 - 40,4	
5 G 35	razno	51.487	2.716	1.680.0	37,0 - 42,0	
H01N2-D	Gumom oplašten kabel za zavarivanje, normalnog stupnja fleksibilnosti					
	1 x 16	razno	5.112	205	153.6	8,8 - 11,5
	1 x 25	razno	6.926	302	240.0	10,1 - 13,0
	1 x 35	razno	9.305	420	336.0	11,4 - 14,5
	1 x 50	razno	13.110	586	480.0	13,2 - 17,0
	1 x 70	razno	19.135	798	672.0	15,3 - 19,2
	1 x 95	razno	25.124	1.015	912.0	17,1 - 21,5
H05RNH2-F	Plosnati gumom oplašten kabel za ukrasnu rasvjetu					
	2 x 2,5	razno	3.752	147	48	5,7 x 13,3
NSSHöu	Gumom izoliran i oplašten 0,6/1 kV kabel za jača mehanička opterećenja i rudnike					
	3 x 1,5	razno	3.886	195	43.2	11.9
	4 x 1,5	razno	5.030	226	57.6	12.7
	5 x 1,5	razno	5.684	264	72.0	13.6
	3 x 2,5	razno	5.493	257	72.0	13.3
	4 x 2,5	razno	6.817	343	96.0	15.5
	5 x 2,5	razno	7.508	402	120.0	16.6
	4 x 4	razno	10.265	440	153.6	17.1
	4 x 6	razno	13.336	549	230.4	18.5
	4 x 10	razno	21.348	855	384.0	22.8
	4 x 16	razno	31.772	1.224	614.4	26.7
	4 x 25	razno	45.222	1.802	960.0	31.9

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
NSSH0u	4 x 35	razno	61.293	2.230	1.344.0	33.7
	4 x 50	razno	82.524	3.201	1.920.0	40.9
	5 x 4	razno	12.193	521	192.0	18.4
	5 x 6	razno	17.199	694	288.0	20.8
	5 x 10	razno	27.456	1.027	480.0	24.6
SiF Silikskom gumom izoliran finožični vodič						
	0.5	100	237	8.6	4.8	2.1
	0.75	100	349	11	7.2	2.4
	1	100	425	13.6	9.6	2.4
	1.5	100	534	20	14.4	2.8
	2.5	100	849	32	24.0	3.4
	4	100	1.441	49	38.4	4.2
	6	100	2.125	71	57.6	5.2
	10	100	3.674	124	96.0	7
	16	100	6.262	188	153.6	8
	25	100	9.811	296	240.0	9.9
	35	100	13.463	400	336.0	11.2
SiHF Silikskom gumom izoliran i oplašten fleksibilni kabel						
	2 x 0,75	razno	1.118	57	14.4	6.4
	3 x 0,75	razno	1.550	66	21.6	6.8
	3 x 1	razno	1.834	78	28.8	7.4
	2 x 1,5	razno	1.695	87	28.8	7.6
	3 x 1,5	razno	2.383	98	43.2	8.0
	4 x 1,5	razno	3.156	122	57.6	8.8
	5 x 1,5	razno	4.370	148	72.0	9.6
	7 x 1,5	razno	5.917	232	100.8	10.9
	3 x 2,5	razno	3.649	152	72.0	9.6
	4 x 2,5	razno	4.877	189	96.0	10.6
	5 x 2,5	razno	6.978	229	120.0	11.6
H07BQ-F Poliuretanom oplašten fleksibilni energetski kabel za gradilišta						
	2 x 1,5	razno	1.999	87.5	28.8	7,6 - 9,8
	3 x 1,5	razno	2.682	107	43.2	8,0 - 10,4
	4 x 1,5	razno	3.190	136	57.6	9,0 - 11,6
	5 x 1,5	razno	3.713	170	72.0	9,8 - 12,7
	3 x 2,5	razno	3.726	159	72.0	9,6 - 12,4
	4 x 2,5	razno	4.863	206	96.0	10,7 - 13,8
	5 x 2,5	razno	6.243	258	120.0	11,9 - 15,3
	3 x 4	razno	5.949	228	115.2	11,3 - 14,5
	5 x 4	razno	9.358	345	192.0	14,1 - 17,9
	5 x 6	razno	13.390	518	288.0	15,7 - 20,0
H07Z-K Bezhalogeni finožični vodič, poboljšanih svojstava za slučaj požara						
	1.5	100	435	20	14.4	2,8 - 3,5
	2.5	100	692	31	24.0	3,4 - 4,3
	4	100	1.051	46	38.4	3,9 - 4,9
	6	100	1.523	65	57.6	4,4 - 5,5
	10	100	2.589	110	96.0	5,7 - 7,1
	16	razno	3.957	170	153.6	6,7 - 8,4
	25	razno	6.096	260	240.0	8,4 - 10,6
	35	razno	8.462	360	336.0	9,7 - 12,1
	50	razno	12.115	515	480.0	11,5 - 14,4
	70	razno	16.912	710	672.0	13,2 - 16,6
	95	razno	22.417	940	912.0	15,2 - 18,8
	120	razno	28.528	1.180	1.152.0	16,7 - 20,9
	150	razno	34.928	1.600	1.440.0	18,6 - 23,3
	185	razno	44.009	2.100	1.776.0	20,6 - 25,8
	240	razno	58.045	3.015	2.304.0	23,5 - 29,4
NHXMH Bezhalogeni instalacijski kabel, 300/500V, poboljšanih svojstava za slučaj požara						
	2 x 1,5	500	1.090	120	28.8	9.0
	3 x 1,5	500	1.357	133	43.2	9.8
	4 x 1,5	500	2.019	157	57.6	10.5
	5 x 1,5	500	2.316	183	72.0	11.5
	7 x 1,5	500	3.835	250	100.8	11

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
NHXMH	3 x 2,5	500	1.990	176	72.0	11
	5 x 2,5	500	3.463	249	120.0	12.5
	3 x 4	razno	3.724	247	115.2	12.5
	3 x 6	razno	5.535	335	172.8	14
	5 x 4	razno	6.107	370	192.0	15.5
	5 x 6	razno	8.736	488	288.0	16.5
	5 x 10	razno	13.348	739	480.0	18
	5 x 16	razno	21.522	1.142	768.0	23
N2XH	Bezhalogeni energetska i signalna 0,6/1 kV kabel, poboljšanih svojstava za slučaj požara					
	1 x 16	razno	5.055	202	154.0	9.1
	1 x 25	razno	7.427	302	240.0	11
	1 x 35	razno	10.002	397	336.0	12
	1 x 50	razno	13.583	523	480.0	13
	1 x 70	razno	18.485	745	672.0	15
	1 x 95	razno	26.263	986	912.0	17
	1 x 120	razno	28.988	1.214	1.152.0	18
	1 x 150	razno	36.330	1.536	1.440.0	21
	1 x 185	razno	44.484	1.888	1.776.0	23
	1 x 240	razno	57.945	2.472	2.304.0	26
	1 x 300	razno	69.370	2.945	2.880.0	28
	2 x 1,5	razno	1.275	120	29.0	9
	2 x 2,5	razno	1.900	154	48.0	10
	3 x 1,5	razno	1.451	135	43.0	9
	3 x 2,5	razno	2.035	181	72.0	10
	3 x 4	razno	3.349	242	115.0	11
	3 x 6	razno	5.228	319	173.0	13
	3 x 10	razno	9.038	464	288.0	14
	4 x 1,5	razno	2.072	163	58.0	10
	4 x 2,5	razno	3.098	214	96.0	11
	4 x 4	razno	4.786	294	154.0	12
	4 x 6	razno	6.891	390	230.0	14
	4 x 10	razno	11.948	586	384.0	16
	4 x 16	razno	18.379	874	614.0	19
	4 x 25	razno	26.910	1.332	960.0	23
	4 x 35	razno	36.771	1.777	1.344.0	26
	4 x 50	razno	49.306	2.343	1.920.0	29
	4 x 70	razno	69.882	3.384	2.688.0	35
	4 x 95	razno	95.802	4.490	3.648.0	39
	4 x 120	razno	119.704	5.558	4.608.0	43
	4 x 150	razno	142.252	6.998	5.760.0	48
	4 x 185	razno	175.252	8.657	7.104.0	53
	4 x 240	razno	223.339	11.385	9.216.0	60
	5 x 1,5	razno	2.243	193	72.0	11
	5 x 2,5	razno	3.334	256	120.0	12
	5 x 4	razno	5.567	352	192.0	13
	5 x 6	razno	7.765	475	288.0	15
	5 x 10	razno	12.355	708	480.0	17
	5 x 16	razno	19.630	1.081	768.0	21
	5 x 25	razno	29.466	1.631	1.200.0	26
	5 x 35	razno	44.115	2.163	1.680.0	29
	7 x 1,5	razno	3.686	300	100.8	15
	10 x 1,5	razno	5.726	360	144	19
	12 x 1,5	razno	6.698	400	172.8	20
	7 x 2,5	razno	7.978	420	168	16
FG16OM16	Bezhalogeni 0,6/1 kV kabel izoliran visokokvalitetnom G16 HEPR smjesom					
	3 G 1,5	razno	1.741	139	43.2	12.5
	3 G 2,5	razno	2.566	185	72.0	13.6
	3 G 4	razno	3.740	246	115.2	14.9
	3 G 6	razno	5.361	313	172.8	16.2
	3 G 10	razno	8.572	503	288.0	18.2
	3 G 16	razno	12.979	609	460.8	20.6
	5 G 1,5	razno	2.683	204	72.0	14.4

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
FG16OM16	5 G 2,5	razno	3.969	266	120.0	15.6
	5 G 4	razno	5.898	361	192.0	17.3
	5 G 6	razno	8.533	471	288.0	18.9
	5 G 10	razno	13.761	756	480.0	21.5
	5 G 16	razno	20.918	1.119	768.0	24.4
NHXX FE180 / E90			Bezhalogeni 0,6/1 kV kabel, s električnom funkcijom od 90 min			
	1 x 25	razno	7.804	347	240.0	11.7
	1 x 35	razno	10.286	449	336.0	12.8
	1 x 50	razno	13.425	589	480.0	14.3
	1 x 70	razno	20.726	810	672.0	16.1
	1 x 95	razno	24.970	1.090	912.0	18.5
	1 x 120	razno	35.051	1.318	1.152.0	19.6
	1 x 150	razno	37.623	1.648	1.440.0	21.8
	1 x 185	razno	49.362	2.029	1.776.0	24
	1 x 240	razno	68.724	2.658	2.304.0	27.2
	2 x 1,5	razno	1.660	178	29.0	11
	3 x 1,5	razno	2.165	200	43.0	11.5
	3 x 2,5	razno	3.171	250	72.0	12.4
	3 x 4	razno	4.720	319	115.0	13.5
	3 x 6	razno	6.672	403	173.0	14.6
	4 x 1,5	razno	3.088	234	58.0	12.4
	4 x 2,5	razno	4.088	296	96.0	13.4
	4 x 4	razno	6.299	381	154.0	14.6
	4 x 6	razno	8.599	490	230.0	15.8
	4 x 10	razno	14.384	695	384.0	17.8
	4 x 16	razno	21.700	1.089	614.0	22.1
	4 x 25	razno	34.088	1.618	960.0	26.3
	4 x 35	razno	44.462	2.083	1.344.0	29
	4 x 50	razno	57.896	2.752	1.920.0	32.8
	4 x 70	razno	82.049	3.804	2.688.0	37.6
	4 x 95	razno	111.396	5.092	3.648.0	43.1
	4 x 120	razno	137.620	6.133	4.608.0	46
	4 x 150	razno	174.622	7.662	5.760.0	51.2
	4 x 185	razno	218.466	9.425	7.104.0	56.5
	4 x 240	razno	285.515	12.334	9.216.0	64.1
	5 x 1,5	razno	3.538	278	72.0	13.4
	5 x 2,5	razno	4.761	353	120.0	14.5
	5 x 4	razno	7.155	456	192.0	15.8
	5 x 6	razno	9.887	589	288.0	17.2
	5 x 10	razno	16.165	832	480.0	19.3
	5 x 16	razno	24.169	1.361	768.0	24.8
	5 x 25	razno	36.873	1.960	1.200.0	28.8
	5 x 35	razno	53.894	2.547	1.680.0	32
	7 x 1,5	razno	4.846	331	101.0	15.8
	7 x 2,5	razno	8.034	426	168.0	17.7
BXO-HFTG			Brodski teškogorivi kabel bez halogena 0,6/1 kV			
	3 x 1,5	razno	2.242	120	43.2	9
	3 x 2,5	razno	3.326	160	72.0	10
H1Z2Z2-K			Kabel za fotonaponske sustave, AC/DC 1500 V			
	1 x 4	500	1.167	58.2	38.4	6.6
	1 x 6	500	1.668	79	57.6	7.4
	1 x 10	500	2.775	128	96.0	8.8
SOLAR MC4 konektor			Konektori za PV kabele			
	4 F 1000 V (4 ... 6mm2)	100	1.277	9.5		
	4 M 1000 V (4 ... 6mm2)	100	1.277	11		
	4 F GEN2 1500 V (4 ... 6mm2)	100	1.329	11.2		
	4 M GEN2 1500 V (4 ... 6mm2)	100	1.329	13.1		
LiYCY			Elektronički fleksibilni kabel izoliran i oplašten PVC-om, s Cu opletom			
	2 x 0,25	razno	596	28	16.0	4.6
	3 x 0,25	razno	598	34	21.0	4.8
	4 x 0,25	razno	898	40	24.0	5.2
	5 x 0,25	razno	1.043	47	29.0	5.7

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
LiYCY	6 x 0,25	razno	1.235	54	32.0	6.3
	7 x 0,25	razno	1.169	61	37.0	6.3
	8 x 0,25	razno	1.621	66	42.0	6.4
	10 x 0,25	razno	1.961	80	50.0	6.7
	2 x 0,5	100, razno	781	35	23.0	5.2
	3 x 0,5	100, razno	1.092	55	39.0	5.3
	4 x 0,5	100, razno	1.301	61	46.0	5.7
	5 x 0,5	razno	1.643	76	57.0	6.4
	7 x 0,5	razno	2.321	98	80.0	7
	10 x 0,5	razno	2.793	135	100.0	8.8
	12 x 0,5	razno	3.422	157	117.0	9.5
	2 x 0,75	100, razno	791	59	38.0	5.7
	3 x 0,75	100, razno	1.153	66	50.0	5.9
	4 x 0,75	100, razno	1.391	77	58.0	6.5
	5 x 0,75	100, razno	1.804	93	70.0	7
	7 x 0,75	100, razno	2.496	130	100.0	7.8
	8 x 0,75	razno	2.899	145	110.0	8.6
	10 x 0,75	razno	4.861	180	140.0	9.7
	12 x 0,75	razno	4.168	202	154.0	10.2
	2 x 1	100, razno	1.066	65	46.0	6
	3 x 1	100, razno	1.620	80	56.0	6.5
	4 x 1	100, razno	1.796	98	69.0	7.1
	5 x 1	100, razno	2.516	127	89.0	7.8
	7 x 1	razno	3.178	158	118.0	8.5
	8 x 1	razno	3.975	197	130.0	9.4
	10 x 1	razno	5.553	232	145.0	10.8
	12 x 1	razno	5.721	260	168.0	11.2
	2 x 1,5	100, razno	1.472	88	63.0	7.7
	3 x 1,5	100, razno	2.114	100	76.0	7.9
	4 x 1,5	100, razno	2.712	126	108.0	8
	5 x 1,5	razno	3.552	160	129.0	8.8
	7 x 1,5	razno	4.434	208	164.0	9.6
LiYCY-TP	Elektronički PVC fleksibilni kabel, s Cu opletom, s uvijenim paricama					
	2 x 2 x 0,5	razno	1.579	93	54.0	7.3
	3 x 2 x 0,5	razno	1.872	129	74.0	8.4
	4 x 2 x 0,5	razno	2.666	146	91.0	9.4
	6 x 2 x 0,5	razno	4.807	198	120.0	11.2
	8 x 2 x 0,5	razno	5.957	259	144.0	11.5
	12 x 2 x 0,5	razno	6.873	354	199.0	15.1
	2 x 2 x 0,75	razno	1.918	106	58.0	9.5
	3 x 2 x 0,75	razno	2.514	140	85.0	9.6
	4 x 2 x 0,75	razno	3.034	179	108.0	10.3
	6 x 2 x 0,75	razno	6.230	246	146.0	12.4
LiHCH	Elektronički bezhalogeni fleksibilni kabel, s Cu opletom					
	2 x 0,75	razno	909	59	38.0	5.7
	3 x 0,75	razno	1.160	66	50.0	5.9
	4 x 0,75	razno	1.404	77	58.0	6.5
	5 x 0,75	razno	1.783	93	70.0	7
	7 x 0,75	razno	2.368	130	100.0	7.8
	2 x 1	razno	1.050	65	46.0	6
	3 x 1	razno	1.412	80	56.0	6.5
	4 x 1	razno	1.837	98	69.0	7.1
	5 x 1	razno	2.225	127	89.0	7.8
	7 x 1	razno	3.024	158	118.0	8.5
	2 x 1,5	razno	1.444	88	63.0	7.7
	3 x 1,5	razno	1.921	100	76.0	7.9
	4 x 1,5	razno	2.498	126	108.0	8
	5 x 1,5	razno	3.048	160	129.0	8.8
	7 x 1,5	razno	4.138	208	164.0	9.6
YSLY	Signalni fleksibilni kabel izoliran i oplašten PVC-om					
	2 x 0,5	razno	402	35	9.6	4.8
	3 x 0,5	razno	599	41	14.0	5.1

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
YSLY	4 x 0,5	razno	740	49	19.0	5.5
	5 x 0,5	razno	993	60	24.0	6.2
	7 x 0,5	razno	1.220	77	34.0	6.7
	10 x 0,5	razno	1.858	101	48.0	8.5
	12 x 0,5	razno	2.025	125	58.0	9.1
	14 x 0,5	razno	2.766	131	67.0	9.5
	16 x 0,5	razno	2.749	151	77.0	10.3
	21 x 0,5	razno	4.098	215	101.0	11.2
	25 x 0,5	razno	4.549	252	120.0	12.6
	2 x 0,75	razno	525	42	14.0	5.2
	3 x 0,75	razno	703	51	22.0	5.5
	4 x 0,75	razno	932	63	29.0	6.2
	5 x 0,75	razno	1.178	78	36.0	6.7
	6 x 0,75	razno	1.567	85	43.0	7.3
	7 x 0,75	razno	1.650	95	50.0	7.5
	10 x 0,75	razno	2.489	150	72.0	9.6
	12 x 0,75	razno	2.839	165	86.0	9.8
	16 x 0,75	razno	3.847	195	115.0	11.1
	21 x 0,75	razno	5.262	288	151.0	12.5
	25 x 0,75	razno	6.179	330	180.0	14
	34 x 0,75	razno	8.668	435	245.0	16.3
	2 x 1	razno	690	52	19.0	5.6
	3 x 1	razno	927	65	29.0	6.1
	4 x 1	razno	1.216	78	38.0	6.7
	5 x 1	razno	1.533	95	48.0	7.5
	7 x 1	razno	2.111	120	67.0	8.1
	10 x 1	razno	3.163	180	96.0	10.2
	12 x 1	razno	3.504	235	115.0	10.9
	14 x 1	razno	3.873	238	134.0	11.2
	16 x 1	razno	5.013	266	154.0	11.9
	18 x 1	razno	5.625	298	173.0	12.9
	21 x 1	razno	6.823	366	202.0	13.8
	25 x 1	razno	7.571	400	240.0	15.4
	34 x 1	razno	11.153	535	326.0	17.9
	2 x 1,5	razno	944	65	29.0	6.4
	3 x 1,5	razno	1.192	80	43.0	6.8
	4 x 1,5	razno	1.634	102	58.0	7.6
	5 x 1,5	razno	2.033	125	72.0	8.3
	7 x 1,5	razno	2.841	166	101.0	9.2
	10 x 1,5	razno	4.349	243	144.0	11.6
	12 x 1,5	razno	5.126	272	173.0	12.4
	14 x 1,5	razno	6.289	323	202.0	12.7
	16 x 1,5	razno	6.781	361	230.0	13.4
	18 x 1,5	razno	8.012	402	259.0	14.8
	21 x 1,5	razno	9.028	484	302.0	15.6
	25 x 1,5	razno	10.739	555	360.0	17.6
	34 x 1,5	razno	14.951	750	490.0	20.2
	2 x 2,5	razno	1.515	99	48.0	7.6
	3 x 2,5	razno	2.071	128	72.0	8.3
	4 x 2,5	razno	2.727	159	96.0	9
	5 x 2,5	razno	3.361	199	120.0	10.1
	7 x 2,5	razno	4.834	258	168.0	11.2
	10 x 2,5	razno	7.146	310	240.0	13
	12 x 2,5	razno	8.778	361	288.0	15
	18 x 2,5	razno	12.994	519	432.0	18
	3 x 4	razno	3.276	169	115.0	10
	4 x 4	razno	4.441	242	154.0	11
	4 x 6	razno	6.515	340	230.0	13
	4 x 10	razno	10.849	577	384.0	17
	4 x 16	razno	17.819	1.022	614.0	21
	5 x 4	razno	5.684	302	192.0	12.5
	5 x 6	razno	8.528	424	288.0	14

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
YSLY	5 x 10	razno	14.461	717	480.0	18.5
	5 x 16	razno	22.342	1.370	768.0	22.5
	7 x 4	razno	7.783	407	269.0	13.4
	7 x 6	razno	11.675	600	403.0	16
YSLCY	Signalni fleksibilni PVC kabel, sa Cu zaslonom					
	2 x 0,75	razno	1.128	59	39.0	6.2
	3 x 0,75	razno	1.328	66	49.0	6.2
	4 x 0,75	razno	1.581	77	57.0	6.7
	5 x 0,75	razno	2.075	93	70.0	7.4
	7 x 0,75	razno	2.597	130	98.0	8.6
	12 x 0,75	razno	4.079	202	151.0	10.7
	16 x 0,75	razno	5.505	275	172.0	12
	25 x 0,75	razno	7.926	415	271.0	15.6
	34 x 0,75	razno	11.775	535	370.0	17.2
	2 x 1	razno	1.248	65	55.0	6.7
	3 x 1	razno	1.613	80	70.0	7
	4 x 1	razno	2.034	98	80.0	7.1
	5 x 1	razno	2.386	127	95.0	8.5
	7 x 1	razno	3.276	158	120.0	9.7
	10 x 1	razno	4.373	232	138.0	12
	12 x 1	razno	4.988	260	186.0	12.4
	14 x 1	razno	6.385	302	198.0	13
	18 x 1	razno	6.827	380	245.0	14.5
	25 x 1	razno	8.808	534	342.0	18
	2 x 1,5	razno	1.481	88	65.0	7.3
	3 x 1,5	razno	2.076	100	90.0	7.7
	4 x 1,5	razno	2.476	126	110.0	8.3
	5 x 1,5	razno	3.199	160	125.0	9.4
	7 x 1,5	razno	4.144	208	159.0	10.7
	12 x 1,5	razno	6.899	338	254.0	13.6
	18 x 1,5	razno	9.538	479	367.0	16.3
	25 x 1,5	razno	14.038	705	492.0	20.3
	2 x 2,5	razno	2.179	130	98.0	9
	3 x 2,5	razno	3.350	167	148.0	9.9
	4 x 2,5	razno	3.798	195	174.0	10.2
	5 x 2,5	razno	5.075	223	200.0	11.6
	7 x 2,5	razno	6.863	344	235.0	13.7
	12 x 2,5	razno	9.763	570	440.0	18.2
	4 x 4	razno	6.014	310	290.0	12.9
	4 x 6	razno	8.459	415	360.0	14.7
	4 x 10	razno	13.546	731	535.0	18.9
	4 x 16	razno	20.033	993	809.0	20.8
	5 x 4	razno	6.759	385	328.0	14.3
	5 x 6	razno	9.390	509	441.0	16.4
BUS kabeli	Kabeli za Profibus i KNX sustave					
	BUS PB 1 x 2 x 0,64	razno	2.384	74	30.1	8.0
	BUS EIB / KNX 2 x 2 x 0,8	razno	791	54	21.0	6.6
Kabel za alarme	Kabel za alarme					
	4 x 0,22	100	312	21	8.45	3.6
	6 x 0,22	100	315	26	12.67	4.1
	8 x 0,22	100	496	33	16.90	4.5
	12 x 0,22	100	634	45	25.34	5.35
	4 x 0,22 + 2 x 0,5	100	461	35	18.05	4.65
	6 x 0,22 + 2 x 0,75	razno	661	50	27.07	5.35
	12 x 0,22 + 2 x 0,75	razno	1.040	66	38.74	6.3
Kabel za zvučnike	Kabel za zvučnike					
	2 x 0,5	100	197	21	9.6	2,4 x 4,8
	2 x 0,75	100	250	29	14.0	2,5 x 5,0
	2 x 1	100	407	32	19.0	2,6 x 5,2
	2 x 1,5	100	532	42	29.0	2,7 x 5,6
	2 x 2,5	100	892	61	48.0	3,6 x 7,4
	2 x 4	100	1.717	110	77.0	4,5 x 9,7

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
YYSch Telekomunikacijski instalacijski kabel s izolacijom i plaštom od PVC-a						
	2 x 0,6	100	287	12	5.6	3,1 - 3,7
	3 x 0,6	100	400	16	8.4	3,4 - 3,9
	4 x 0,6	100	506	20	11.2	3,5 - 4,1
	5 x 0,6	100	608	26	14.0	4,1 - 4,3
	6 x 0,6	100	712	29	16.8	4,6 - 4,7
	10 x 0,6	100	1.140	54	28.0	5,5 - 6,7
J-Y(St)Y Telekomunikacijski instalacijski PVC kabel, sa zaslonom od Al-folije						
	1 x 2 x 0,6	250	312	30	7.0	5.0
	2 x 2 x 0,6	250	463	40	13.0	5.5
	3 x 2 x 0,6	250	710	50	18.0	6.3
	4 x 2 x 0,6	100, 250	796	60	24.0	6.8
	5 x 2 x 0,6	100, 250	1.062	70	30.0	7.2
	6 x 2 x 0,6	100	1.235	80	35.0	7.5
	10 x 2 x 0,6	razno	1.954	110	58.0	9.0
	20 x 2 x 0,6	razno	3.655	190	116.0	11.0
	30 x 2 x 0,6	razno	5.841	280	172.0	13.0
	50 x 2 x 0,6	razno	8.919	440	286.0	17.0
	100 x 2 x 0,6	razno	17.845	850	568.0	23.0
	1 x 2 x 0,8	250	443	40	11.0	6.0
	2 x 2 x 0,8	100, 250, 500	656	60	21.0	7.0
	3 x 2 x 0,8	100, 250	1.051	80	31.0	8.5
	4 x 2 x 0,8	100, 250	1.307	100	41.0	9.0
	5 x 2 x 0,8	100, 250	1.781	120	52.0	9.5
	6 x 2 x 0,8	100	2.102	140	62.0	10.5
	10 x 2 x 0,8	razno	3.374	210	102.0	13.0
	20 x 2 x 0,8	razno	6.349	380	204.0	16.5
	30 x 2 x 0,8	razno	9.820	550	304.0	20.0
JB-Y(St)Y Vatrodojavni instalacijski PVC kabel, sa zaslonom od Al-folije						
	1 x 2 x 0,8	100, 500	420	40	11.0	6.0
	2 x 2 x 0,8	100, 500	649	60	21.0	7.0
	4 x 2 x 0,8	500, razno	1.399	100	41.0	9.0
J-H(St)Y Bezhalogeni telekomunikacijski kabel, poboljšanih svojstava za slučaj požara						
	2 x 2 x 0,8	razno	851	69	25.0	7.0
	2 x 2 x 0,8 (crveni)	razno	851	69	25.0	7.0
	4 x 2 x 0,8	razno	1.666	136	45.0	9.0
	4 x 2 x 0,8 (crveni)	razno	1.666	136	45.0	9.0
JE-H(St)H FE180 / E30-E90 Bezhalogeni kabel za industrijsku elektroniku, s funkcijom od 30 i 90 minuta						
	1 x 2 x 0,8	razno	874	40	15.0	5.5
	2 x 2 x 0,8	razno	1.241	56	25.0	6.6
	4 x 2 x 0,8	razno	2.461	96	45.0	8.7
TK 59-50 xDSL Telekom, distributivni kabel, vanjski, niskofrekventni za širokopojasne usluge						
	2 x 2 x 0,5	razno	856	55	7.0	7.5
	6 x 2 x 0,5	razno	1.621	95	20.8	9.8
	10 x 2 x 0,5	razno	2.567	125	34.8	11.0
	20 x 2 x 0,5	razno	4.622	200	69.5	12.9
	50 x 2 x 0,5	razno	10.109	270	173.8	17.8
TK 59U-50 xDSL Telekom, samonosivi distributivni kabel, niskofrekventni za širokopojasne usluge						
	6 x 2 x 0,5	razno	2.272	130	20.8	9,4 x 16,7
F-2YA2Y Telekomunikacijski kabel za vanjsku uporabu, podzemni						
	2 x 2 x 0,8	razno	997	55	25	7.3
	6 x 2 x 0,8	razno	2.444	115	62	10.4
	10 x 2 x 0,8	razno	3.779	170	102	12.0
Koax 75 Ohm Koaksijalni kabel 75 Ohm						
	CATV 1,13/4,8 AF Tri-Shld	100, 500	742	50	18.5	6.8
	CATV 1,13/4,8 AF Tri-Shld LSOH	100	846	50	18.5	6.8
	RG 6	100	248	41	15.0	6.8
	RG 11	razno	1.593	135	62.6	10.1
	RG 59 B/U	100	484	54	24.7	6.15
	KOAX6 CT 15 A PE podzemni	razno	2.625	102	56.0	10.1
Koax 50 Ohm Koaksijalni kabel 50 Ohm						
	RG 58 C/U 50 Ohm	100	704	37	20	4.95

Tip	Konstrukcija	Pakovanje	Cijena (EUR/km)	Težina (kg/km)	Al-Cu (kg/km)	Promjer (mm)
Koax 50 Ohm	RG 213 U 50 Ohm	razno	3.067	157	87	10.3
Cat.5e 200 Mhz			LAN kabel kategorije 5e, do 200 MHz			
	U/UTP PVC	305, 500	500	35	17.5	4,9 - 5,1
	U/UTP LSOH	500	582	36	17.5	4,9 - 5,1
	F/UTP PVC	500	652	36	19.8	5,9 - 6,6
	F/UTP LSOH	500	742	37	19.8	5,9 - 6,6
	SF/UTP LSOH	500	1.103	47	27	6,4 - 6,6
	U/UTP PE outdoor	500	748	39	12	7.5
	F/UTP PE outdoor	500	932	39	12	7.5
	U/UTP flex	500	766	26	11	5.2
	F/UTP flex	500	914	26	12	5.4
Cat. 6 350 Mhz			LAN kabel kategorije 6, do 350 MHz			
	U/UTP PVC	305, 500	621	39	20.5	6,2 - 6,8
	U/UTP LSOH	500	657	40	20.5	6,2 - 6,8
	U/FTP PVC	500	869	41	24.0	6,5 - 7,6
	U/FTP LSOH	500	895	44	24.0	6,5 - 7,6
	S/FTP LSOH	500	1.124	49	34.0	7,4 - 8,2
	U/UTP PE outdoor	500	864	39	20.5	7.5
Cat. 6A 500 Mhz			LAN kabel kategorije 6A, do 500 MHz			
	U/FTP LSOH	500	995	44	24.0	6.5
Cat. 7 800 Mhz			LAN kabel kategorije 7, do 800 MHz			
	S/FTP LSOH	500	1.090	55	26.0	7,3 - 8,0
	S/FTP PE outdoor	500	1.599	62	26.0	8.3
Multimode			Svjetlovodni Unitube kabel sa MM nitima, s ojačanjem i zaštitom od glodavaca			
	4 G 50 / 125 OM2	razno	825	40		5.8
	8 G 50 / 125 OM2	razno	1.168	40		5.8
	12 G 50 / 125 OM2	razno	1.508	40		5.8
	24 G 50 / 125 OM2	razno	2.764	45		6.9
	4 G 50 / 125 OM3	razno	1.234	40		5.8
	8 G 50 / 125 OM3	razno	2.419	40		5.8
Singlemode			Svjetlovodni kabel s SM nitima, Unitube / Stranded loose tube, za vanjsku upotrebu			
	1 x 4E9 / 125 4 niti G.657a	razno	779	7		2.5
	3 x 4E9 / 125 12 niti G.652d	razno	768	75		9.6
	6 x 4E9 / 125 24 niti G.652d	razno	996	78		9.6
	6 x 8E9 / 125 48 niti G.652d	razno	1.554	97		11.3
	8 x 12E9 / 125 96 niti G.652d	razno	4.272	97		11.8